

屋内照明器具特性	
品番 (品名)	YYY41000+YYY90251
光源	LLD3020LCE1 ×2 795.0 lm
管理番号	K0194459 (1) D 1
BZ分類	BZ1

器具効率		21 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) ZCM																				
保守率		良 中 否	0.63	0.6	15	14	13	12	14	13	12	12	13	12	12	11	12	11	11	11	10				
			0.6	0.8	16	15	14	13	15	14	13	13	13	13	12	12	12	12	11	11	10				
			0.56	1.0	17	15	15	14	16	15	14	13	14	13	13	12	12	12	12	11	10				
			1.25	17	16	15	15	16	15	15	14	14	14	13	13	13	12	12	12	10					
下方投影面積		cm ²	1.5	18	17	16	15	17	16	15	15	15	14	14	13	13	13	12	12	12	10				
			2.0	18	18	17	16	17	17	16	16	15	15	14	14	13	13	13	13	12	10				
等価発光面積		cm ²	2.5	19	18	17	17	18	17	17	16	15	15	15	14	13	13	13	13	10					
			3.0	19	18	18	17	18	17	17	16	16	15	15	15	15	13	13	13	13	10				
H _m	0.37H _m	0.37H _m	4.0	19	19	18	18	18	18	17	17	16	15	15	15	13	13	13	13	10					
			5.0	20	19	19	19	18	18	18	17	16	16	15	15	14	13	13	13	10					
			7.0	20	20	19	19	19	18	18	18	16	16	16	16	14	14	14	13	10					
			10.0	20	20	20	19	19	19	18	18	16	16	16	16	14	14	14	14	10					

