

屋内照明器具特性	
品番 (品名)	XS Z D1 0 0 0 V
光源	LLD2400VCB1 ×1 500.0 lm
管理番号	K0191450 (0) DB 1
B Z 分類	BZ2

器具効率		95 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z CM																
保守率		良 中 否	0.67	0.6	63	54	48	43	62	53	47	43	60	52	47	43	58	51	47	43	41
			0.63	0.8	73	65	59	55	72	64	59	55	70	63	58	54	68	62	57	54	53
			0.56	1.0	79	72	66	62	78	71	66	62	76	70	65	62	74	68	65	61	60
				1.25	84	77	73	69	83	77	72	69	80	75	71	68	78	74	70	68	66
下方投影面積		cm ²	1.5	87	81	77	73	86	80	76	73	83	79	75	72	81	78	74	72	70	
			2.0	91	86	82	79	90	85	82	79	87	84	81	78	85	82	80	77	75	
等価発光面積		cm ²	2.5	93	89	86	83	92	88	85	83	90	87	84	82	88	85	83	81	79	
			3.0	95	91	89	86	94	91	88	86	91	89	87	85	89	87	85	83	81	
H m	1.26 H m	1.26 H m	4.0	97	94	92	90	96	93	91	89	93	91	90	88	91	90	88	87	84	
			5.0	98	96	94	92	97	95	93	91	95	93	91	90	92	91	90	89	86	
			7.0	99	98	96	95	98	97	95	94	96	95	94	93	94	93	92	91	88	
			10.0	100	99	98	97	99	98	97	96	97	96	95	94	95	94	93	93	90	

