

| 屋内照明器具特性 |                         |
|----------|-------------------------|
| 品番 (品名)  | XS Z D3 0 0 0 V         |
| 光源       | LLD3400VCB1 ×1 700.0 lm |
| 管理番号     | K0191487 ( 0 ) DB 1     |
| B Z 分類   | BZ3 / 0.7 / BZ2         |

| 器具効率     |                     | 96 %            | 反射率    | 天井              | 80 %               |     |     |    | 70 % |     |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|----------|---------------------|-----------------|--------|-----------------|--------------------|-----|-----|----|------|-----|----|----|------|----|----|----|------|----|----|----|-----|
|          |                     |                 |        | 壁               | 70                 | 50  | 30  | 10 | 70   | 50  | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|          |                     |                 |        | 床               | 10 %               |     |     |    | 10 % |     |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|          |                     |                 |        | 室指数             | 照明率 ( X0.01 ) Z CM |     |     |    |      |     |    |    |      |    |    |    |      |    |    |    |     |
| 保守率      |                     | 良<br>中<br>否     | 0.67   | 0.6             | 63                 | 54  | 47  | 43 | 62   | 53  | 47 | 43 | 60   | 52 | 47 | 43 | 59   | 51 | 46 | 43 | 41  |
|          |                     |                 | 0.63   | 0.8             | 74                 | 65  | 59  | 55 | 72   | 64  | 59 | 55 | 70   | 63 | 58 | 54 | 68   | 62 | 58 | 54 | 53  |
|          |                     |                 | 0.56   | 1.0             | 80                 | 72  | 67  | 63 | 79   | 72  | 66 | 63 | 76   | 70 | 66 | 62 | 74   | 69 | 65 | 62 | 60  |
|          |                     |                 |        | 1.25            | 85                 | 78  | 73  | 69 | 84   | 78  | 73 | 69 | 81   | 76 | 72 | 69 | 79   | 75 | 71 | 68 | 67  |
| 下方投影面積   |                     | cm <sup>2</sup> |        | 1.5             | 88                 | 82  | 78  | 74 | 87   | 81  | 77 | 74 | 85   | 80 | 76 | 73 | 82   | 78 | 75 | 73 | 71  |
|          |                     |                 | 等価発光面積 | cm <sup>2</sup> | 2.0                | 92  | 87  | 84 | 80   | 91  | 87 | 83 | 80   | 89 | 85 | 82 | 79   | 87 | 83 | 81 | 78  |
| 取付<br>高さ | 器具間隔最大限             |                 |        | 2.5             | 95                 | 91  | 87  | 85 | 93   | 90  | 87 | 84 | 91   | 88 | 85 | 83 | 89   | 86 | 84 | 82 | 80  |
|          | 横方向 ( A ) 縦方向 ( B ) |                 |        | 3.0             | 96                 | 93  | 90  | 87 | 95   | 92  | 89 | 87 | 93   | 90 | 88 | 86 | 91   | 88 | 86 | 85 | 82  |
| H m      | 1.31 H m 1.31 H m   |                 |        | 4.0             | 98                 | 96  | 93  | 91 | 97   | 95  | 93 | 91 | 95   | 93 | 91 | 89 | 93   | 91 | 89 | 88 | 86  |
|          |                     |                 |        | 5.0             | 100                | 97  | 95  | 94 | 98   | 96  | 95 | 93 | 96   | 94 | 93 | 91 | 94   | 93 | 91 | 90 | 88  |
|          |                     |                 |        | 7.0             | 101                | 99  | 98  | 96 | 100  | 98  | 97 | 96 | 97   | 96 | 95 | 94 | 95   | 94 | 93 | 92 | 90  |
|          |                     |                 |        | 10.0            | 102                | 101 | 100 | 99 | 101  | 100 | 99 | 98 | 99   | 98 | 97 | 96 | 96   | 96 | 95 | 94 | 92  |

