

| 屋内照明器具特性 |                          |
|----------|--------------------------|
| 品番 (品名)  | XSZP3567V+LGK9100B       |
| 光源       | LLD3411VCB1 ×1 700.0 l m |
| 管理番号     | K0191396 ( 0 ) DB 1      |
| B Z 分類   | BZ1                      |

| 器具効率   |           | 97 %             | 反射率       | 天井            | 80 % |     |     |     | 70 % |     |     |     | 50 % |     |    |    | 30 % |    |    |    | 0 % |   |   |   |
|--------|-----------|------------------|-----------|---------------|------|-----|-----|-----|------|-----|-----|-----|------|-----|----|----|------|----|----|----|-----|---|---|---|
|        |           |                  |           | 壁             | 70   | 50  | 30  | 10  | 70   | 50  | 30  | 10  | 70   | 50  | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |   |   |   |
|        |           |                  |           | 床             | 10 % |     |     |     | 10 % |     |     |     | 10 % |     |    |    | 10 % |    |    |    | 0 % |   |   |   |
| 上方光束   |           | 0 %              | 室指数       | 照明率 ( X0.01 ) |      |     |     |     |      |     |     |     |      |     |    |    |      |    |    |    |     | Z | C | M |
| 下方光束   |           | 97 %             |           |               |      |     |     |     |      |     |     |     |      |     |    |    |      |    |    |    |     |   |   |   |
| 保守率    |           | 良                | 0.67      | 0.6           | 88   | 84  | 81  | 79  | 87   | 83  | 81  | 79  | 86   | 83  | 80 | 79 | 85   | 82 | 80 | 79 | 78  |   |   |   |
|        |           | 中                | 0.63      | 0.8           | 92   | 88  | 86  | 84  | 91   | 88  | 85  | 83  | 90   | 87  | 85 | 83 | 89   | 86 | 84 | 83 | 82  |   |   |   |
|        |           | 否                | 0.56      | 1.0           | 95   | 91  | 89  | 87  | 94   | 91  | 88  | 87  | 92   | 90  | 88 | 86 | 91   | 89 | 87 | 86 | 85  |   |   |   |
|        |           |                  |           | 1.25          | 97   | 94  | 91  | 90  | 96   | 93  | 91  | 89  | 94   | 92  | 90 | 89 | 93   | 91 | 90 | 88 | 87  |   |   |   |
| 下方投影面積 |           | c m <sup>2</sup> |           | 1.5           | 98   | 95  | 93  | 91  | 97   | 95  | 93  | 91  | 96   | 93  | 92 | 90 | 94   | 92 | 91 | 90 | 89  |   |   |   |
| 等価発光面積 |           | c m <sup>2</sup> |           | 2.0           | 100  | 97  | 96  | 94  | 99   | 97  | 95  | 94  | 97   | 95  | 94 | 93 | 95   | 94 | 93 | 92 | 90  |   |   |   |
| 取付高さ   | 器具間隔最大限   |                  |           | 2.5           | 101  | 99  | 97  | 96  | 100  | 98  | 97  | 95  | 98   | 97  | 95 | 94 | 96   | 95 | 94 | 93 | 92  |   |   |   |
|        | 横方向 ( A ) |                  | 縦方向 ( B ) | 3.0           | 101  | 100 | 98  | 97  | 100  | 99  | 98  | 97  | 99   | 97  | 96 | 95 | 97   | 96 | 95 | 94 | 92  |   |   |   |
| H m    | 0.79 H m  |                  | 0.79 H m  | 4.0           | 102  | 101 | 100 | 99  | 101  | 100 | 99  | 98  | 99   | 98  | 98 | 97 | 97   | 97 | 96 | 95 | 93  |   |   |   |
|        |           |                  |           | 5.0           | 103  | 102 | 101 | 100 | 102  | 101 | 100 | 99  | 100  | 99  | 98 | 98 | 98   | 97 | 97 | 96 | 94  |   |   |   |
|        |           |                  |           | 7.0           | 103  | 102 | 101 | 100 | 102  | 101 | 100 | 100 | 100  | 99  | 99 | 98 | 98   | 97 | 97 | 95 |     |   |   |   |
|        |           |                  |           | 10.0          | 104  | 103 | 103 | 102 | 103  | 102 | 101 | 101 | 101  | 100 | 99 | 99 | 98   | 98 | 98 | 95 |     |   |   |   |

