

屋内照明器具特性	
品番 (品名)	YYY41000
光源	LLD40402CQ1 (KAKUSAN) ×2 860.0 lm
管理番号	K0194448 (1) D 1
BZ分類	BZ1

器具効率		1 2 % 上方光束 6 % 下方光束 6 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 3	0 . 6	1 . 0	1 . 2 5	0 . 5 6	2 . 0	2 . 5	3 . 0	4 . 0	5 . 0	7 . 0	1 0 . 0	1 1	1 1	1 1	1 1	1 0 . 0		
			7	8	8	9	1 0	1 0	1 0	1 0	1 1	1 1	1 1	1 1	1 1	1 1	1 1	1 1	1 1	1 1	
			6	7	8	8	9	9	9	9	9	9	9	9	9	9	9	9	9	9	
			5	6	7	8	8	9	9	9	9	9	9	9	9	9	9	9	9	9	
下方投影面積		c m ²	1 . 5	2 . 0	2 . 5	3 . 0	4 . 0	5 . 0	7 . 0	1 0 . 0	1 1	1 1	1 1	1 1	1 1	1 1	1 1	1 1	1 0 . 0		
等価発光面積			c m ²	9	1 0	1 0	1 0	1 0	1 0	1 0	1 0	1 0	1 0	1 0	1 0	1 0	1 0	1 0	1 0		
					9	9	9	9	9	9	9	9	9	9	9	9	9	9	9		
						8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	
取付高さ		器具間隔最大限				H m	0 . 5 5 H m	0 . 5 5 H m													
横方向 (A)		縦方向 (B)																			

