

屋内照明器具特性	
品番 (品名)	YYY41000
光源	LLD5010LCC1 ×2 1095.0 lm
管理番号	K0194457 (1) D 1
BZ分類	BZ1

器具効率		73 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束		37 %	室指数	照明率 (X0.01) ZCM																		
下方光束		36 %																				
保守率		良 中 否	0.63	0.6	49	44	41	39	47	43	40	38	42	39	37	36	38	36	34	33	30	
			0.6	0.8	54	49	45	43	51	46	44	42	45	42	40	39	40	38	37	36	31	
				1.0	56	52	49	46	53	49	47	44	47	44	42	41	41	40	38	37	32	
			0.56	1.25	59	55	52	49	55	52	49	47	49	46	45	43	43	41	40	39	33	
下方投影面積		cm ²		1.5	61	57	54	52	57	54	51	49	50	48	46	45	43	42	41	40	33	
			等価発光面積	cm ²	2.0	63	60	57	55	59	56	54	52	51	50	48	47	44	43	42	42	34
取付 高さ	器具間隔最大限			2.5	64	62	60	58	60	58	56	55	52	51	50	49	45	44	43	43	34	
	横方向 (A)		縦方向 (B)	3.0	65	63	61	59	61	59	58	56	53	52	51	50	46	45	44	43	34	
H m	0.80 H m	0.79 H m		4.0	67	65	63	62	62	61	59	58	54	53	52	51	46	46	45	44	35	
				5.0	68	66	65	63	63	62	61	60	55	54	53	52	46	46	46	45	35	
				7.0	68	67	66	65	64	63	62	61	55	55	54	53	47	47	46	46	35	
				10.0	69	68	68	67	65	64	63	63	56	55	55	54	47	47	47	46	35	

