

屋内照明器具特性																				
品番 (品名)		YYY46024Z+YYY96222Z_WI DE																		
光源		LED4000_70_2200 ×1 2200.0 l m																		
管理番号		K0148445 (0) DB 1																		
B Z 分類		BZ5 / 0.7 / BZ6 / 0.9 / BZ7 / 1.1 / BZ9 / 1.4 / BZ1																		
器具効率 上方光束 下方光束	100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
	100 %		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	0 %		床	10 %				10 %				10 %				10 %				0 %
			室指数	照明率 (X0.01) Z C M																
保守率	良 0.69 中 0.67 否 0.63	0.6	43	33	26	22	37	28	23	19	25	19	16	13	14	11	9	8	0	
		0.8	51	41	34	29	43	35	29	25	29	24	21	18	17	14	12	11	0	
		1.0	56	47	40	35	48	40	35	31	33	28	24	22	19	16	14	13	0	
		1.25	61	53	47	42	52	46	40	36	36	31	28	25	20	18	16	15	0	
下方投影面積 等価発光面積	cm ²	1.5	65	57	51	46	56	49	44	40	38	34	31	28	22	20	18	17	0	
	cm ²	2.0	70	63	58	54	60	55	50	47	41	38	35	33	24	22	21	19	0	
取付高さ	器具間隔最大限		2.5	73	67	63	59	63	58	54	51	43	40	38	36	25	23	22	21	0
	横方向 (A)	縦方向 (B)	3.0	75	70	66	62	64	61	57	54	44	42	40	38	26	24	23	22	0
H m	0.00 H m	0.00 H m	4.0	78	74	71	67	67	64	61	59	46	44	43	41	27	26	25	24	0
			5.0	79	76	73	71	68	66	63	61	47	46	44	43	27	27	26	25	0
			7.0	81	79	77	75	70	68	66	65	49	47	46	45	28	28	27	27	0
			10.0	83	81	80	78	72	70	69	68	50	49	48	47	29	28	28	28	0
配光曲線 ランプ光束1000 lm			直射水平面照度 ランプ光束1000 lm																	
			80 lx																	
			60																	
			40																	
			20																	
			10																	
			8																	
			6																	
			4																	
			2																	
			.8																	
			.6																	
			.4																	
			.2																	
			A 8 m 6 4 2 0 2 4 6 8 A'																	