

| 屋内照明器具特性 |                             |
|----------|-----------------------------|
| 品番 (品名)  | YYY46024M                   |
| 光源       | LED4000_70_3240 ×1 3240.0lm |
| 管理番号     | K0181307 (0) DR1            |
| BZ分類     | BZ10                        |

| 器具効率             |           | 100 %<br><br>上方光束<br>下方光束          | 100 %<br><br>0 % | 反射率  | 天井  | 80 %             |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|------------------|-----------|------------------------------------|------------------|------|-----|------------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|                  |           |                                    |                  |      | 壁   | 70               | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|                  |           |                                    |                  |      | 床   | 10 %             |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|                  |           |                                    |                  |      | 室指数 | 照明率 ( X0.01) ZCM |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |
| 保守率              |           | 良<br>中<br>否                        | 0.69             | 0.6  | 43  | 33               | 26 | 22 | 37 | 28   | 23 | 19 | 25 | 19   | 16 | 13 | 14 | 11   | 9  | 8  | 0  |     |
|                  |           |                                    | 0.67             | 0.8  | 51  | 41               | 34 | 29 | 43 | 35   | 30 | 25 | 29 | 24   | 21 | 18 | 17 | 14   | 12 | 11 | 0  |     |
|                  |           |                                    | 0.63             | 1.0  | 56  | 47               | 40 | 35 | 48 | 41   | 35 | 31 | 33 | 28   | 24 | 22 | 19 | 16   | 14 | 13 | 0  |     |
|                  |           |                                    | 0.63             | 1.25 | 61  | 53               | 47 | 42 | 52 | 46   | 40 | 36 | 36 | 31   | 28 | 26 | 20 | 18   | 16 | 15 | 0  |     |
| 下方投影面積<br>等価発光面積 |           | cm <sup>2</sup><br>cm <sup>2</sup> | 1.5              | 65   | 57  | 51               | 47 | 56 | 49 | 44   | 40 | 38 | 34 | 31   | 28 | 22 | 20 | 18   | 17 | 0  |    |     |
|                  |           |                                    | 2.0              | 70   | 63  | 58               | 54 | 60 | 55 | 50   | 47 | 41 | 38 | 35   | 33 | 24 | 22 | 21   | 19 | 0  |    |     |
| 取付<br>高さ         | 器具間隔最大限   |                                    |                  | 2.5  | 73  | 67               | 63 | 59 | 63 | 58   | 54 | 51 | 43 | 40   | 38 | 36 | 25 | 23   | 22 | 21 | 0  |     |
|                  | 横方向 ( A ) |                                    | 縦方向 ( B )        | 3.0  | 75  | 70               | 66 | 62 | 65 | 61   | 57 | 54 | 44 | 42   | 40 | 38 | 26 | 24   | 23 | 22 | 0  |     |
| H m              | 0.20 H m  |                                    | 0.20 H m         | 4.0  | 78  | 74               | 71 | 68 | 67 | 64   | 61 | 59 | 46 | 44   | 43 | 41 | 27 | 26   | 25 | 24 | 0  |     |
|                  |           |                                    |                  | 5.0  | 80  | 76               | 73 | 71 | 68 | 66   | 64 | 61 | 47 | 46   | 44 | 43 | 27 | 27   | 26 | 25 | 0  |     |
|                  |           |                                    |                  | 7.0  | 81  | 79               | 77 | 75 | 70 | 68   | 67 | 65 | 49 | 48   | 46 | 45 | 28 | 28   | 27 | 27 | 0  |     |
|                  |           |                                    |                  | 10.0 | 83  | 81               | 80 | 78 | 72 | 70   | 69 | 68 | 50 | 49   | 48 | 47 | 29 | 29   | 28 | 28 | 0  |     |

