

屋内照明器具特性	
品番 (品名)	YYY20663K
光源	LED3000_70_660 ×1 660.0 lm
管理番号	K0178713 (1) DR1
BZ分類	BZ5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		9 % 9 1 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6 9	0 . 6	5 4	4 1	3 3	2 8	5 2	4 0	3 3	2 7	4 9	3 8	3 2	2 7	4 6	3 7	3 1	2 6	2 4	
			0 . 6 7	0 . 8	6 3	5 1	4 3	3 7	6 1	5 0	4 3	3 7	5 7	4 8	4 1	3 6	5 4	4 6	4 0	3 5	3 2	
			0 . 6 3	1 . 0	7 0	5 9	5 1	4 4	6 8	5 7	5 0	4 4	6 3	5 4	4 8	4 3	5 9	5 2	4 6	4 2	3 8	
				1 . 2 5	7 6	6 5	5 8	5 2	7 3	6 4	5 7	5 1	6 9	6 1	5 5	5 0	6 5	5 8	5 3	4 8	4 5	
下方投影面積		cm ²	1 . 5	8 0	7 0	6 3	5 7	7 7	6 9	6 2	5 6	7 3	6 5	6 0	5 5	6 9	6 2	5 7	5 3	4 9		
等価発光面積		cm ²	2 . 0	8 5	7 7	7 1	6 5	8 3	7 6	6 9	6 4	7 8	7 2	6 7	6 2	7 4	6 9	6 4	6 0	5 6		
取付 高さ	器具間隔最大限		2 . 5	8 9	8 2	7 6	7 1	8 7	8 0	7 5	7 0	8 2	7 6	7 2	6 8	7 7	7 3	6 9	6 6	6 1		
	横方向 (A) 縦方向 (B)		3 . 0	9 2	8 5	8 0	7 5	8 9	8 3	7 9	7 4	8 4	8 0	7 5	7 2	8 0	7 6	7 3	6 9	6 5		
1 . 5m	1 . 9 7 m	1 . 9 9 m	4 . 0	9 5	9 0	8 5	8 1	9 2	8 8	8 4	8 0	8 8	8 4	8 0	7 7	8 3	8 0	7 7	7 5	7 0		
2	2 . 6 3	2 . 6 3	5 . 0	9 7	9 3	8 9	8 5	9 5	9 1	8 7	8 4	9 0	8 7	8 4	8 1	8 5	8 3	8 0	7 8	7 3		
2 . 5	3 . 3	3 . 2 7	7 . 0	9 9	9 6	9 3	9 0	9 7	9 4	9 1	8 9	9 2	9 0	8 8	8 5	8 8	8 6	8 4	8 2	7 7		
3	3 . 9 6	3 . 9 1	1 0 . 0	1 0 1	9 9	9 7	9 4	9 9	9 7	9 5	9 3	9 4	9 3	9 1	8 9	9 0	8 9	8 7	8 6	8 1		

