

屋内照明器具特性	
品番 (品名)	YYY41000
光源	LLD4000LCE1 ×2 845.0 lm
管理番号	K0194440 (2) D 1
BZ分類	BZ1

器具効率		14 % 上方光束 7 % 下方光束 7 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
				室指数	照明率 (X0.01) ZCM																	
保守率		良 中 否	0.63	0.6	0.56	0.6	9	7	7	6	8	7	6	6	7	6	6	6	5	5	4	
			0.6	0.8	1.0	9	8	7	9	8	7	7	8	7	7	6	7	7	6	6	5	
			0.56	1.0	1.0	9	9	8	10	9	8	8	9	8	7	7	7	7	7	6	5	
			0.56	1.25	1.1	1.0	9	9	10	10	9	8	9	8	8	8	8	7	7	7	6	
下方投影面積		cm ²	1.5	1.1	1.1	1.0	9	1.1	1.0	9	9	9	9	8	8	8	8	7	7	6		
等価発光面積			cm ²	2.0	1.2	1.1	1.1	1.0	1.1	1.1	1.0	1.0	1.0	9	9	9	8	8	8	8	6	
取付高さ	器具間隔最大限			2.5	1.2	1.2	1.1	1.1	1.2	1.1	1.1	1.0	1.0	1.0	9	9	9	8	8	8	6	
	横方向 (A)			縦方向 (B)		3.0	1.3	1.2	1.2	1.1	1.2	1.1	1.1	1.1	1.0	1.0	1.0	9	9	8	8	6
H m		0.72 H m		0.72 H m	4.0	1.3	1.2	1.2	1.2	1.2	1.2	1.1	1.1	1.1	1.0	1.0	1.0	1.0	9	9	9	8
				5.0	1.3	1.3	1.2	1.2	1.2	1.2	1.2	1.1	1.1	1.0	1.0	1.0	1.0	9	9	9	9	7
				7.0	1.3	1.3	1.3	1.3	1.2	1.2	1.2	1.2	1.2	1.1	1.0	1.0	1.0	9	9	9	9	7
				10.0	1.3	1.3	1.3	1.3	1.2	1.2	1.2	1.2	1.2	1.1	1.1	1.1	1.0	9	9	9	9	7

