

| 屋内照明器具特性 |                                   |
|----------|-----------------------------------|
| 品番 (品名)  | YYY41000                          |
| 光源       | LLD40402CQ1 (SHUKOU) ×2 620.0 l m |
| 管理番号     | K0194449 (1) D 1                  |
| BZ分類     | BZ1                               |

| 器具効率     |          | 58 %            | 反射率       | 天井   | 80 %             |     |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|----------|----------|-----------------|-----------|------|------------------|-----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|          |          |                 |           | 壁    | 70               | 50  | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|          |          |                 |           | 床    | 10 %             |     |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|          |          |                 |           | 室指数  | 照明率 ( X0.01) ZCM |     |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |
| 保守率      |          | 良<br>中<br>否     | 0.63      | 0.6  | 38               | 33  | 30 | 28 | 36   | 32 | 29 | 27 | 32   | 29 | 27 | 26 | 28   | 26 | 25 | 24 | 22  |
|          |          |                 | 0.6       | 0.8  | 41               | 37  | 34 | 32 | 39   | 35 | 33 | 31 | 35   | 32 | 30 | 29 | 31   | 29 | 28 | 27 | 23  |
|          |          |                 |           | 1.0  | 44               | 40  | 37 | 35 | 41   | 38 | 36 | 34 | 37   | 34 | 33 | 31 | 32   | 31 | 29 | 29 | 24  |
|          |          |                 | 0.56      | 1.25 | 46               | 43  | 40 | 38 | 43   | 40 | 38 | 36 | 38   | 36 | 35 | 33 | 33   | 32 | 31 | 30 | 25  |
| 下方投影面積   |          | cm <sup>2</sup> |           | 1.5  | 48               | 45  | 42 | 40 | 45   | 42 | 40 | 38 | 39   | 37 | 36 | 35 | 34   | 33 | 32 | 31 | 26  |
|          |          |                 | 等価発光面積    |      | cm <sup>2</sup>  | 2.0 | 50 | 47 | 45   | 43 | 47 | 44 | 43   | 41 | 41 | 39 | 38   | 37 | 35 | 34 | 33  |
| 取付<br>高さ | 器具間隔最大限  |                 |           |      |                  | 2.5 | 51 | 49 | 47   | 45 | 48 | 46 | 44   | 43 | 42 | 40 | 39   | 38 | 36 | 35 | 34  |
|          |          | 横方向 ( A )       | 縦方向 ( B ) | 3.0  | 52               | 50  | 48 | 47 | 49   | 47 | 46 | 44 | 42   | 41 | 40 | 39 | 36   | 36 | 35 | 34 | 27  |
| H m      | 0.70 H m | 0.69 H m        | 4.0       | 53   | 51               | 50  | 49 | 50 | 48   | 47 | 46 | 43 | 42   | 41 | 41 | 37 | 36   | 36 | 35 | 28 |     |
|          |          |                 | 5.0       | 54   | 52               | 51  | 50 | 50 | 49   | 48 | 47 | 43 | 43   | 42 | 42 | 37 | 37   | 36 | 36 | 28 |     |
|          |          |                 | 7.0       | 54   | 53               | 53  | 52 | 51 | 50   | 49 | 49 | 44 | 44   | 43 | 43 | 38 | 37   | 37 | 37 | 28 |     |
|          |          |                 | 10.0      | 55   | 54               | 54  | 53 | 51 | 51   | 50 | 50 | 44 | 44   | 44 | 43 | 38 | 38   | 37 | 37 | 28 |     |

