

屋内照明器具特性	
品番 (品名)	YYY41000
光源	LLD3000CU1 x2 795.0 lm
管理番号	K0194450 (1) D 1
BZ分類	BZ1

器具効率		16 % 上方光束 8 % 下方光束 8 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						照明率 (X0.01) Z CM																
保守率		良 中 否	0.63 0.6 0.56	0.6	9	8	7	6	9	7	7	6	8	7	6	6	7	6	6	5	5	
				0.8	10	9	8	8	10	9	8	7	9	8	7	7	7	7	6	6	5	
				1.0	11	10	9	9	11	10	9	8	9	8	8	7	8	7	7	7	6	
				1.25	12	11	10	9	11	10	10	9	10	9	9	8	8	8	8	7	6	
下方投影面積		cm ²	1.5	12	11	11	10	12	11	10	10	10	9	9	9	9	8	8	8	6		
				2.0	13	12	12	11	12	11	11	10	10	10	10	9	9	9	8	8	6	
取付高さ	器具間隔最大限			2.5	13	13	12	12	12	12	11	11	11	10	10	10	9	9	9	7		
	横方向 (A)		縦方向 (B)		3.0	14	13	13	12	13	12	12	11	11	11	10	9	9	9	7		
H m	0.75 H m		0.74 H m	4.0	14	14	13	13	13	13	12	12	11	11	11	10	9	9	9	7		
				5.0	14	14	13	13	13	13	13	12	11	11	11	11	10	9	9	7		
				7.0	14	14	14	14	13	13	13	13	12	11	11	11	10	10	10	7		
				10.0	15	14	14	14	14	13	13	13	12	12	11	11	10	10	10	7		

