

屋内照明器具特性	
品番 (品名)	YYY41000
光源	LLD5010LCC1 ×2 1095.0 lm
管理番号	K0194457 (1) D 1
BZ分類	BZ1

器具効率		73 %	反射率	天井	80 %				70 %				50 %				30 %				0 %					
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %					
				床	10 %				10 %				10 %				10 %				0 %					
上方光束		37 %	室指数	照明率 (X0.01)																			Z	C		M
下方光束		36 %																								
保守率		良 中 否	0.63	0.6	49	44	41	39	47	43	40	38	42	39	37	36	38	36	34	33	30					
			0.6	0.8	54	49	45	43	51	46	44	42	45	42	40	39	40	38	37	36	31					
				1.0	56	52	49	46	53	49	47	44	47	44	42	41	41	40	38	37	32					
			0.56	1.25	59	55	52	49	55	52	49	47	49	46	45	43	43	41	40	39	33					
下方投影面積		cm ²		1.5	61	57	54	52	57	54	51	49	50	48	46	45	43	42	41	40	33					
			等価発光面積	2.0	63	60	57	55	59	56	54	52	51	50	48	47	44	43	42	42	34					
取付 高さ	器具間隔最大限			2.5	64	62	60	58	60	58	56	55	52	51	50	49	45	44	43	43	34					
	横方向 (A)		縦方向 (B)	3.0	65	63	61	59	61	59	58	56	53	52	51	50	46	45	44	43	34					
H m	0.80 H m	0.79 H m		4.0	67	65	63	62	62	61	59	58	54	53	52	51	46	46	45	44	35					
				5.0	68	66	65	63	63	62	61	60	55	54	53	52	46	46	46	45	35					
				7.0	68	67	66	65	64	63	62	61	55	55	54	53	47	47	46	46	35					
				10.0	69	68	68	67	65	64	63	63	56	55	55	54	47	47	47	46	35					

