

屋内照明器具特性	
品番 (品名)	YYY41000+YYY90250+YYY902
光源	LLD3020LCE1 ×2 795.0 lm
管理番号	K0194462 (1) D 1
BZ分類	BZ1

器具効率		16 % 上方光束 8 % 下方光束 8 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.63	0.6	11	10	9	9	11	10	9	9	10	9	9	8	9	8	8	8	7
			0.6	0.8	12	11	10	10	11	10	10	9	10	10	9	9	9	9	8	8	7
			0.56	1.0	12	12	11	10	12	11	10	10	10	10	10	9	9	9	9	9	7
			1.25	1.3	12	12	11	10	12	12	11	11	11	10	10	10	9	9	9	9	7
下方投影面積 等価発光面積		cm ² cm ²	1.5	1.3	13	12	12	13	12	11	11	11	11	10	10	10	9	9	9	8	
			2.0	1.4	13	13	12	13	12	12	12	11	11	11	10	10	10	9	9	8	
取付 高さ	器具間隔最大限		2.5	1.4	14	13	13	13	13	12	12	12	11	11	11	10	10	10	9	8	
	横方向 (A)	縦方向 (B)	3.0	1.4	14	13	13	13	13	12	12	11	11	11	10	10	10	10	8		
H _m	0.37 H _m	0.37 H _m	4.0	1.5	14	14	14	14	13	13	13	12	12	11	11	10	10	10	8		
			5.0	1.5	14	14	14	14	14	13	13	12	12	12	12	10	10	10	8		
			7.0	1.5	15	15	14	14	14	14	13	12	12	12	12	10	10	10	8		
			10.0	1.5	15	15	15	14	14	14	14	12	12	12	12	10	10	10	8		

