

屋内照明器具特性	
品番 (品名)	YYY41000
光源	LLD20001CQ1 ×2 531.0 lm
管理番号	K0194447 (1) D 1
BZ分類	BZ1

器具効率		16 % 上方光束 8 % 下方光束 8 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
				室指数	照明率 (X0.01) ZCM																	
保守率		良 中 否	0.63	0.6	10	8	8	7	9	8	7	7	8	7	7	6	7	7	6	6	5	
			0.6	0.8	11	10	9	8	10	9	8	8	9	8	8	7	8	7	7	7	6	
			0.56	1.0	12	10	10	9	11	10	9	9	10	9	8	8	8	8	7	7	6	
				1.25	12	11	10	10	11	11	10	9	10	9	9	9	9	8	8	8	6	
下方投影面積		cm ² 等価発光面積 cm ²	1.5	13	12	11	11	12	11	11	10	10	10	9	9	9	9	8	8	7		
			2.0	13	13	12	11	12	12	11	11	11	10	10	10	9	9	9	9	7		
取付			器具間隔最大限	2.5	14	13	12	12	13	12	12	11	11	11	10	10	9	9	9	9	7	
高さ				横方向 (A) 縦方向 (B)	3.0	14	13	13	12	13	13	12	12	11	11	11	10	10	9	9	9	7
H m		0.74 H m			0.74 H m	4.0	14	14	13	13	13	13	12	12	11	11	11	10	10	10	9	7
						5.0	14	14	14	13	13	13	13	12	11	11	11	10	10	10	10	7
					7.0	15	14	14	14	14	13	13	13	12	12	12	11	10	10	10	10	7
				10.0	15	15	14	14	14	14	14	13	12	12	12	12	10	10	10	10	8	

