

屋内照明器具特性	
品番 (品名)	YYY41000
光源	LLD40402CQ1 (KAKUSAN) ×2 860.0 lm
管理番号	K0194448 (1) D 1
BZ分類	BZ1

器具効率		12 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.63	0.6	7	6	5	5	6	6	5	5	6	5	5	4	5	5	4	4	3
			0.6	0.8	8	7	6	6	7	6	6	6	6	5	5	6	5	5	5	5	4
			0.56	1.0	8	8	7	6	8	7	7	6	7	6	6	6	6	6	5	5	4
				1.25	9	8	8	7	8	8	7	7	7	7	6	6	6	6	6	5	4
下方投影面積		cm ²	1.5	9	9	8	8	9	8	8	7	7	7	7	6	6	6	6	6	5	
			2.0	10	9	9	8	9	9	8	8	8	7	7	7	7	7	6	6	6	5
取付高さ	器具間隔最大限		2.5	10	9	9	9	9	9	9	8	8	8	7	7	7	7	6	6	5	
	横方向 (A) 縦方向 (B)		3.0	10	10	9	9	9	9	9	8	8	8	7	7	7	7	6	6	5	
H m	0.55 H m 0.55 H m		4.0	10	10	10	10	10	9	9	8	8	8	8	7	7	7	7	5		
			5.0	11	10	10	10	10	10	9	9	8	8	8	8	7	7	7	5		
			7.0	11	11	10	10	10	10	10	9	9	8	8	8	7	7	7	5		
			10.0	11	11	11	10	10	10	10	10	9	9	9	8	7	7	7	5		

