

屋内照明器具特性	
品番 (品名)	YYY41000
光源	LLD3020LCT1 x2 795.0 l m
管理番号	K0194455 (1) D 1
B Z 分類	BZ1

器具効率		60 %	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
上方光束		30 %	室指数	照明率 (X0.01)																		Z C M
下方光束		30 %																				
保守率		良 中 否	0.63	0.6	41	37	34	32	39	35	33	31	35	33	31	30	32	30	29	28	25	
			0.6	0.8	45	41	38	36	42	39	36	35	38	35	34	32	33	32	31	30	26	
				1.0	47	43	41	38	44	41	39	37	39	37	35	34	35	33	32	31	27	
				0.56	1.25	49	46	43	41	46	43	41	39	41	39	37	36	36	34	33	33	28
下方投影面積		c m ²	1.5	50	47	45	43	47	45	43	41	42	40	39	37	36	35	34	34	28		
等価発光面積			c m ²	2.0	52	50	48	46	49	47	45	44	43	42	40	39	37	36	36	35	29	
取付 高さ	器具間隔最大限		2.5	54	51	50	48	50	48	47	46	44	43	42	41	38	37	36	36	29		
	横方向 (A)		縦方向 (B)	3.0	54	53	51	50	51	49	48	47	44	43	42	42	38	38	37	36	29	
H m	0.41 H m	0.40 H m	4.0	55	54	53	52	52	51	50	49	45	44	44	43	39	38	38	37	29		
			5.0	56	55	54	53	52	51	51	50	45	45	44	44	39	39	38	38	29		
			7.0	57	56	55	54	53	52	52	51	46	46	45	45	39	39	39	39	30		
			10.0	57	57	56	56	54	53	53	52	46	46	46	45	40	39	39	39	30		

