

屋内照明器具特性																					
品番 (品名)		YYY46024Z+YYY96222Z_FRON																			
光源		LED4000_70_2250 ×1 2250.0 lm																			
管理番号		K0148446 (0) DB 1																			
B Z 分類		BZ5/0.7/BZ7/0.9/BZ8/1.1/BZ9 / 1.4/BZ1																			
器具効率 上方光束 下方光束	100 % 100 % 0 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
			床	10 %				10 %				10 %				10 %				0 %	
			室指数	照明率 (X0.01) ZCM																	
保守率	良 0.69 中 0.67 否 0.63	0.6	43	33	26	22	37	28	23	19	25	19	16	13	14	11	9	8	0		
		0.8	51	41	34	29	43	35	29	25	29	24	21	18	17	14	12	11	0		
		1.0	56	47	40	35	48	40	35	31	33	28	24	22	19	16	14	13	0		
		1.25	61	53	47	42	52	46	40	36	36	31	28	25	20	18	16	15	0		
下方投影面積 等価発光面積	cm ² cm ²	1.5	65	57	51	46	56	49	44	40	38	34	31	28	22	20	18	17	0		
		2.0	70	63	58	54	60	55	50	47	41	38	35	33	24	22	21	19	0		
取付高さ	器具間隔最大限		2.5	73	67	63	59	63	58	54	51	43	40	38	36	25	23	22	21	0	
	横方向 (A)	縦方向 (B)	3.0	75	70	66	62	64	61	57	54	44	42	40	38	26	24	23	22	0	
H m	0.00 H m	0.00 H m	4.0	78	74	71	67	67	64	61	59	46	44	43	41	27	26	25	24	0	
			5.0	79	76	73	71	68	66	63	61	47	46	44	43	27	27	26	25	0	
			7.0	81	79	77	75	70	68	66	65	49	47	46	45	28	28	27	27	0	
			10.0	83	81	80	78	72	70	69	68	50	49	48	47	29	28	28	28	0	
配光曲線 ランプ光束1000 lm			直射水平面照度 ランプ光束1000 lm																		
			80 lx																		
			60																		
			40																		
			20																		
			10																		
			8																		
			6																		
			4																		
			2																		
			.8																		
			.6																		
			.4																		
			.2																		
			A 8m 6 4 2 0 2 4 6 8 A'																		