

屋外照明器具特性																			
品番 (品名)		YYY8 0 1 4 2																	
光源		LED4000_85_200 x1 200.0 lm																	
管理番号		K0199192 (0) DR 1																	
JISC8131-1999 による配光形式		CUT - OFF F																	
器具効率		99.9 %				直下光度				0.0 cd/1000lm									
上方光束		10.3%				最大光度				883.2 cd/1000lm									
下方光束		89.6%																	
鉛直角 θ	0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°
φ = 0° 鉛直面	0	0	82	228	333	406	456	514	572	601	661	798	883	849	734	505	179	103	73
90°	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
180°	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
270°	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
I maxを含む鉛直面	0	0	82	228	333	406	456	514	572	601	661	798	883	849	734	505	179	103	73

配光曲線
cd/1000 lm

最大光度 I maxを含む
θ = 60° の円錐面

最大光度 I maxを含む
φ = 0° の鉛直面

パナソニックエレクトリックワークス株式会社