

屋外照明器具特性																				
品番 (品名)		YYY8 1 1 4 2																		
光源		LED4000_85_210 ×1 210.0 lm																		
管理番号		K0199191 (0) DR 1																		
JISC8131-1999 による配光形式		CUT - OFF F																		
器具効率		99.9 %				直下光度				0.0 cd/1000lm										
上方光束		10.2%				最大光度				758.8 cd/1000lm										
下方光束		89.7%																		
鉛直角 θ		0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°
φ = 0° 鉛直面		0	0	40	112	185	256	329	397	461	505	559	682	758	729	619	421	139	75	51
90°		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
180°		0	0	27	71	115	157	187	196	178	138	109	97	91	85	77	62	42	28	20
270°		0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
I maxを含む鉛直面		0	0	40	112	185	256	329	397	461	505	559	682	758	729	619	421	139	75	51

配光曲線
cd/1000 lm

最大光度 I maxを含む
θ = 60° の円錐面

最大光度 I maxを含む
φ = 0° の鉛直面