

Model Name	10GBASE-LR SFP+ Module(i)	Product Specification	401-59024-IN-SP01																																		
Model No.	ZLP59024-IN		Page 1 of 5																																		
1. Summary 10GBASE-LR SFP+ Module(i) is SFP+ (Small-Factor Pluggable) module to be connected to a Panasonic Ethernet Switch's SFP+ extension port. 2. Rated/Environmental Conditions <table><tr><td>2-1. Operating Voltage</td><td>DC 3.3V</td></tr><tr><td>2-2. Power consumption</td><td>1.0W max.</td></tr><tr><td>2-3. Operating environment</td><td>Temperature0 - 60℃ Humidity20 - 80%RH (no condensation)</td></tr><tr><td>2-4. Storage environment</td><td>Temperature-40 - 85℃ Humidity10 - 90%RH (no condensation)</td></tr><tr><td>2-5. Standards</td><td>IEEE802.3ae10GBASE-LR INF-8074i Specification for SFP+ (Small Form Factor Pluggable) Transceiver SFF-8431 Specification for Enhanced Small Form Factor Pluggable Module SFP+ SFF-8432 Specification for Improved Pluggable Form Factor SFF-8472 Diagnostic Monitoring Interface Class 1 Laser Product (EN 60825-1, EN 60825-2) IEC62368-1 EN 55032EN 55035 AS/NZS CISPR32</td></tr></table> 3. Form <table><tr><td>3-1. External Dimensions</td><td>12mm (Height) × 14mm (Width) × 57mm (Depth) (Excluding protruding sections)</td></tr><tr><td>3-2. Mass (Weight)</td><td>18g</td></tr></table> 4. Hardware Specifications <table><tr><td>4-1. Interface</td><td>Fiber port:LC connector (Duplex) , 1port Transmitting and receiving network system:IEEE802.3ae10GBASE-LR Transmission speed:10Gbps Compatible cable:Single Mode Fiber cable Maximum transmission distance:10km</td></tr><tr><td>4-2. Optical wavelength</td><td>1310nm</td></tr><tr><td>4-3. Output Optical Power</td><td>-6.0dBm min. - -0.5dBm max.</td></tr><tr><td>4-4. Optical Input Power minimum (Sensitivity)</td><td>-12.6dBm</td></tr><tr><td>4-5. Diagnostic Monitoring Interface</td><td>SFF-8472 Diagnostic Monitoring Interface for Optical Transceivers (DMI) Ethernet Switch that the device has been installed must have a DMI function too. * 1 Refer 6-1. Supported Products.</td></tr></table> 5. Accessories <table><tr><td>5-1. Accessories</td><td>(1) Installation Guide:1 (2) Protection cap of the fiber optic port (Attached to the module):1</td></tr></table>				2-1. Operating Voltage	DC 3.3V	2-2. Power consumption	1.0W max.	2-3. Operating environment	Temperature0 - 60℃ Humidity20 - 80%RH (no condensation)	2-4. Storage environment	Temperature-40 - 85℃ Humidity10 - 90%RH (no condensation)	2-5. Standards	IEEE802.3ae10GBASE-LR INF-8074i Specification for SFP+ (Small Form Factor Pluggable) Transceiver SFF-8431 Specification for Enhanced Small Form Factor Pluggable Module SFP+ SFF-8432 Specification for Improved Pluggable Form Factor SFF-8472 Diagnostic Monitoring Interface Class 1 Laser Product (EN 60825-1, EN 60825-2) IEC62368-1 EN 55032EN 55035 AS/NZS CISPR32	3-1. External Dimensions	12mm (Height) × 14mm (Width) × 57mm (Depth) (Excluding protruding sections)	3-2. Mass (Weight)	18g	4-1. Interface	Fiber port:LC connector (Duplex) , 1port Transmitting and receiving network system:IEEE802.3ae10GBASE-LR Transmission speed:10Gbps Compatible cable:Single Mode Fiber cable Maximum transmission distance:10km	4-2. Optical wavelength	1310nm	4-3. Output Optical Power	-6.0dBm min. - -0.5dBm max.	4-4. Optical Input Power minimum (Sensitivity)	-12.6dBm	4-5. Diagnostic Monitoring Interface	SFF-8472 Diagnostic Monitoring Interface for Optical Transceivers (DMI) Ethernet Switch that the device has been installed must have a DMI function too. * 1 Refer 6-1. Supported Products.	5-1. Accessories	(1) Installation Guide:1 (2) Protection cap of the fiber optic port (Attached to the module):1	<table><tr><td>Date issued</td><td>June. 21, 2024</td><td rowspan="2">Panasonic Electric Works Networks Co., Ltd.</td></tr><tr><td>Date revised</td><td></td></tr></table>			Date issued	June. 21, 2024	Panasonic Electric Works Networks Co., Ltd.	Date revised	
2-1. Operating Voltage	DC 3.3V																																				
2-2. Power consumption	1.0W max.																																				
2-3. Operating environment	Temperature0 - 60℃ Humidity20 - 80%RH (no condensation)																																				
2-4. Storage environment	Temperature-40 - 85℃ Humidity10 - 90%RH (no condensation)																																				
2-5. Standards	IEEE802.3ae10GBASE-LR INF-8074i Specification for SFP+ (Small Form Factor Pluggable) Transceiver SFF-8431 Specification for Enhanced Small Form Factor Pluggable Module SFP+ SFF-8432 Specification for Improved Pluggable Form Factor SFF-8472 Diagnostic Monitoring Interface Class 1 Laser Product (EN 60825-1, EN 60825-2) IEC62368-1 EN 55032EN 55035 AS/NZS CISPR32																																				
3-1. External Dimensions	12mm (Height) × 14mm (Width) × 57mm (Depth) (Excluding protruding sections)																																				
3-2. Mass (Weight)	18g																																				
4-1. Interface	Fiber port:LC connector (Duplex) , 1port Transmitting and receiving network system:IEEE802.3ae10GBASE-LR Transmission speed:10Gbps Compatible cable:Single Mode Fiber cable Maximum transmission distance:10km																																				
4-2. Optical wavelength	1310nm																																				
4-3. Output Optical Power	-6.0dBm min. - -0.5dBm max.																																				
4-4. Optical Input Power minimum (Sensitivity)	-12.6dBm																																				
4-5. Diagnostic Monitoring Interface	SFF-8472 Diagnostic Monitoring Interface for Optical Transceivers (DMI) Ethernet Switch that the device has been installed must have a DMI function too. * 1 Refer 6-1. Supported Products.																																				
5-1. Accessories	(1) Installation Guide:1 (2) Protection cap of the fiber optic port (Attached to the module):1																																				
Date issued	June. 21, 2024	Panasonic Electric Works Networks Co., Ltd.																																			
Date revised																																					

Model Name	10GBASE-LR SFP+ Module(i)	Product Specification	401-59024-IN-SP01						
Model No.	ZLP59024-IN		Page 2 of 5						
6. Supported Products									
6-1. Supported Products		Please use in Panasonic Ethernet Switches listed below. <table><tr><td>Supported Product Name</td><td>Supported Product Number</td></tr><tr><td>XG-MU24T</td><td>ZLP91240-IN (*1 Supported DMI function)</td></tr><tr><td>XG-MU24TPoE+</td><td>ZLP91249-IN (*1 Supported DMI function)</td></tr></table> For the latest information about supported product, check our website. *1 DMI: Diagnostic Monitoring Interface		Supported Product Name	Supported Product Number	XG-MU24T	ZLP91240-IN (*1 Supported DMI function)	XG-MU24TPoE+	ZLP91249-IN (*1 Supported DMI function)
Supported Product Name	Supported Product Number								
XG-MU24T	ZLP91240-IN (*1 Supported DMI function)								
XG-MU24TPoE+	ZLP91249-IN (*1 Supported DMI function)								
</									

Model Name	10GBASE-LR SFP+ Module(i)	Product Specification	401-59024-IN-SP01
Model No.	ZLP59024-IN		Page 3 of 5
7. Prohibitions when Using the Product to Guarantee Safety Denotes that “Death or serious injuries might be sustained”. The manufacturer assumes no responsibility for any problems occurring when the following conditions are not satisfied. Observe the following items when using the product. (1) Do not handle this SFP+ Module and connection cables during a thunderstorm. Deviation could lead to electric shock. (2) Do not disassemble and/or modify this SFP+ Module. Deviation could lead to fire, electric shock, and/or equipment failure. (3) Do not connect or disconnect this SFP+ Module from the SFP+ extension ports with wet hands. Deviation could lead to electric shock, or malfunctions. (4) Do not insert, nor drop foreign objects such as metal or combustible things into the inside from the openings. Deviation could lead to fire, electric shock, and/or equipment failure. (5) Do not store or use the SFP+ Module in places where it might get splashed with liquids such as water, in places with a lot of humidity, in places with conductive dust, or in places where there are corrosive and combustible gases. Deviation could lead to fire, electric shock, and/or equipment failure. (6) Do not place this SFP+ Module under direct sunlight and/or high temperature. Deviation could lead to high internal temperature and fire. (7) Do not store nor use the SFP+ Module in unstable places where there are lots of vibrations, or impacts. Deviation could lead to falling, injury and/or equipment failure. (8) Do not put the SFP+ Module into fire. Deviation could lead to explosion and/or fire. (9) If the Product is going to be used in high temperature environments, do not perform the following operations with bare hands. - Moving the product from the installation area, or transporting it - Connecting and disconnecting the product, or plugging in or unplugging the fiber optic cables Deviation could lead to injuries or burns, etc. because of high temperatures. (10) Do not connect any instruments other than those which conform to the standards for fiber optic ports. Deviation could lead to fire, electric shock, or malfunctions. (11) Do not look at the laser light. Deviation could lead to visual impairment. (Class 1 Laser Product)			
Date issued	June. 21, 2024	Panasonic Electric Works Networks Co., Ltd.	
Date revised			

Model Name	10GBASE-LR SFP+ Module(i)	Product Specification	401-59024-IN-SP01
Model No.	ZLP59024-IN		Page 4 of 5
8. Cautions when Using the Product to Guarantee Safety Denotes that “Minor injuries might be sustained, or property damage might occur”. The manufacturer assumes no responsibility for any problems occurring when the following conditions are not satisfied. Observe the following items when using the product. (1) If fiber optic cables are going to be connected to this product, check that the fiber optic cable connectors are not contaminated with dust, etc. If they are contaminated, the optical signals will not be properly transmitted, which might cause misoperations, or malfunctions. If they are contaminated, be sure to clean them, then connect them to the fiber optic ports. (2) Be careful in handling the product’s levers and metal terminals, etc. so that you do not cut your hands. (3) This SFP+ Module is to be periodically serviced in order to maintain its performance. Please choose a product administrator, and have them be sure to implement periodic maintenance. (4) When using this SFP+ Module for applications which require extremely high reliability, be careful to expend all possible means to ensure safety and reliability. This SFP+ Module was not designed nor manufactured with the intention that it be used for applications (in use with railways, aviation, and medical care, etc. whereas the influence rate due to communications failures is extremely high in regard to systems that directly affect systems and human lives) which require extremely high reliability. (5) Be aware of glitches which are caused in the usage environments such as age-related degradation, etc. This may vary depending upon conditions such as utilization rates and usage environments, but performance might decrease due to the age-related degradation, etc. of components. It is recommended that this SFP+ Module be replaced about five years after it has been installed. (6) Be careful in regards to environmental restrictions whereby the SFP+ Module can be used. Please isolate the business power lines and communications lines. Isolate distribution lines and other distribution lines, and low current power lines, fiber optic cables, metallic water conduits, and gas conduits, etc. Noise may be generated in the communications lines which might cause communications glitches. (7) Be careful when performing the following operations since the device will be at high temperatures immediately after it has been energized or the power has been shut off. – Moving the product from the installation area, or transporting it – Connecting and disconnecting the product, or plugging in or unplugging the fiber optic cables Deviation could lead to injuries or burns, etc. because of high temperatures.			
Date issued	June. 21, 2024	Panasonic Electric Works Networks Co., Ltd.	
Date revised			

Model Name	10GBASE-LR SFP+ Module(i)	Product Specification	401-59024-IN-SP01
Model No.	ZLP59024-IN		Page 5 of 5
9. Basic Instructions for the Use of This Product (1) For inspection and/or replacement, consult the technical support. (2) Please properly and firmly connect the devices into the Panasonic Ethernet Switch’s SFP+ extension ports which are compatible with the SFP+ Module. If the SFP+ Module is connected to Ethernet Switches other than Panasonic Ethernet Switches which are compatible with the SFP+ Module, please note that operations are not guaranteed. (3) If the SFP+ Module is going to be disconnected from the SFP+ extension ports, first unlock the cable latches then disconnect the fiber optic cables, lower the SFP+ Module’s levers forward, then with the SFP+ Module’s latches unlocked, pull out the SFP+ Module. (4) Remove the SFP+ Module from the SFP+ extension port before cleaning the SFP+ Module. (5) If fiber optic cables are going to be connected to this product, check that the fiber optic cable connectors are not contaminated with dust, etc. and if they are contaminated, be sure to clean them, then connect them to the fiber optic ports. (6) Do not touch the SFP+ Module’s metal terminals, nor allow charged objects to get close to them. Deviation could lead to malfunctions due to static electricity. (7) Do not put a strong shock, including dropping, to this SFP+ Module. Deviation could lead to equipment failure. (8) Do not store and/or use this SFP+ Module in the environment with the characteristics listed below. (Store and/or use this SFP+ Module in the environment in accordance with the specification.) - High humidity. Possible spilled liquid (water). - Dusty. Possible static charge (such as carpet). - Under direct sunlight. - Possible condensation. High/low temperature exceeding the specifications environment. - Strong vibration and/or strong shock. (9) Do not use the SFP+ Module in any condition where the specification limits are exceeded. Deviation could lead to malfunctions.			
Date issued	June. 21, 2024	Panasonic Electric Works Networks Co., Ltd.	
Date revised			