

屋内照明器具特性	
品番 (品名)	L G B 1 0 9 0 7
光源	L G B 1 0 9 0 7 × 1 2 1 6 . 0 l m
管理番号	K 0 1 3 0 3 1 3 (0) D B 1
B Z 分類	B Z 5 / 0 . 7 / B Z 4 / 6 . 0 / B Z 5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		1 2 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		8 8 %																					
保守率		良 中 否	0 . 6 7	0 . 6	5 7	4 5	3 7	3 2	5 5	4 4	3 7	3 2	5 1	4 2	3 6	3 1	4 8	4 0	3 4	3 0	2 8		
			0 . 6 3	0 . 8	6 7	5 6	4 9	4 3	6 5	5 5	4 8	4 3	6 1	5 2	4 6	4 2	5 7	5 0	4 5	4 1	3 7		
			0 . 5 6	1 . 0	7 4	6 4	5 7	5 1	7 1	6 2	5 6	5 1	6 7	5 9	5 4	4 9	6 3	5 7	5 2	4 8	4 4		
				1 . 2 5	7 9	7 0	6 4	5 9	7 7	6 9	6 3	5 8	7 2	6 5	6 0	5 6	6 8	6 2	5 8	5 4	5 0		
下方投影面積		c m ²	1 . 5	8 3	7 5	6 9	6 4	8 1	7 3	6 7	6 3	7 6	7 0	6 5	6 1	7 2	6 6	6 2	5 9	5 5			
等価発光面積		c m ²	2 . 0	8 8	8 2	7 6	7 1	8 6	8 0	7 4	7 0	8 1	7 6	7 1	6 8	7 6	7 2	6 8	6 5	6 1			
取付 高さ	器具間隔最大限		2 . 5	9 1	8 6	8 1	7 7	8 9	8 4	7 9	7 5	8 4	7 9	7 6	7 2	7 9	7 6	7 3	7 0	6 5			
	横方向 (A)		縦方向 (B)		3 . 0	9 4	8 8	8 4	8 0	9 1	8 6	8 2	7 9	8 6	8 2	7 9	7 6	8 1	7 8	7 5	7 3	6 8	
H m	1 . 3 9 H m	1 . 3 9 H m	4 . 0	9 6	9 2	8 9	8 5	9 4	9 0	8 7	8 4	8 9	8 6	8 3	8 0	8 4	8 2	7 9	7 7	7 2			
			5 . 0	9 8	9 5	9 2	8 9	9 5	9 2	8 9	8 7	9 0	8 8	8 6	8 3	8 6	8 4	8 2	8 0	7 4			
			7 . 0	1 0 0	9 7	9 5	9 3	9 7	9 5	9 3	9 1	9 2	9 0	8 9	8 7	8 8	8 6	8 5	8 3	7 7			
			1 0 . 0	1 0 2	1 0 0	9 8	9 6	9 9	9 7	9 6	9 4	9 4	9 3	9 1	9 0	8 9	8 8	8 7	8 6	8 0			

