

屋内照明器具特性	
品番 (品名)	L G B 5 1 5 1 0
光源	LED5000_70_450 ×1 450.0 l m
管理番号	K0141819 (0) DB 1
B Z 分類	B Z 5

器具効率		1 0 0 % 上方光束 4 % 下方光束 9 6 %		反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
					壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
				室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6 3	0 . 6	0 . 6	5 6	4 4	3 6	3 1	5 5	4 3	3 6	3 1	5 2	4 2	3 5	3 0	4 9	4 1	3 4	3 0	2 8	
			0 . 6	0 . 8	6 6	5 5	4 7	4 1	6 4	5 4	4 6	4 1	6 1	5 2	4 5	4 0	5 8	5 0	4 4	4 0	3 7		
			0 . 5 6	1 . 0	7 3	6 2	5 4	4 9	7 1	6 1	5 4	4 8	6 7	5 9	5 3	4 8	6 4	5 7	5 1	4 7	4 4		
				1 . 2 5	7 9	6 9	6 2	5 6	7 7	6 8	6 1	5 6	7 3	6 6	6 0	5 5	7 0	6 3	5 8	5 4	5 1		
下方投影面積		c m ²		1 . 5	8 3	7 4	6 7	6 2	8 1	7 3	6 6	6 1	7 7	7 0	6 5	6 0	7 4	6 8	6 3	5 9	5 6		
等価発光面積		c m ²		2 . 0	8 8	8 1	7 5	7 0	8 6	8 0	7 4	6 9	8 3	7 7	7 2	6 8	7 9	7 4	7 0	6 7	6 3		
取付 高さ	器具間隔最大限			2 . 5	9 2	8 6	8 0	7 6	9 0	8 4	7 9	7 5	8 6	8 1	7 7	7 3	8 3	7 9	7 5	7 2	6 8		
	横方向 (A)		縦方向 (B)	3 . 0	9 4	8 9	8 4	8 0	9 2	8 7	8 3	7 9	8 9	8 4	8 1	7 7	8 5	8 2	7 8	7 6	7 2		
H m	1 . 2 6 H m		1 . 2 6 H m	4 . 0	9 7	9 3	8 9	8 6	9 6	9 1	8 8	8 5	9 2	8 9	8 5	8 3	8 9	8 6	8 3	8 1	7 7		
				5 . 0	9 9	9 6	9 2	8 9	9 7	9 4	9 1	8 8	9 4	9 1	8 8	8 6	9 1	8 8	8 6	8 4	8 0		
				7 . 0	1 0 2	9 9	9 6	9 4	1 0 0	9 7	9 5	9 3	9 6	9 4	9 2	9 0	9 3	9 1	9 0	8 8	8 4		
				1 0 . 0	1 0 3	1 0 1	9 9	9 7	1 0 1	1 0 0	9 8	9 6	9 8	9 7	9 5	9 4	9 5	9 4	9 2	9 1	8 7		

