

屋内照明器具特性	
品番 (品名)	LBJ70076
光源	LBJ70076 ×1                      3.0 l m
管理番号	K0130298 ( 0 ) DD 1
BZ分類	BZ10

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	50 %	反射率	床	10 %				10 %				10 %				10 %				0 %	
下方光束	50 %		室指数	照明率 ( X0.01)                                      ZCM																	
保守率	良	中	0.63	0.6	4.2	2.9	2.1	1.5	3.8	2.7	1.9	1.4	3.1	2.2	1.5	1.1	2.4	1.7	1.2	0.8	0.3
	0.6		0.8	5.0	3.7	2.8	2.2	4.6	3.4	2.6	2.0	3.7	2.8	2.1	1.6	2.9	2.2	1.7	1.3	0.6	
	0.56		1.0	5.6	4.4	3.4	2.8	5.1	4.0	3.2	2.5	4.1	3.2	2.6	2.1	3.2	2.6	2.0	1.6	0.8	
			1.25	6.2	5.0	4.1	3.4	5.6	4.5	3.7	3.1	4.6	3.7	3.1	2.6	3.6	2.9	2.4	2.0	1.1	
下方投影面積	cm <sup>2</sup>	1.5	6.6	5.5	4.6	3.9	6.0	5.0	4.2	3.6	4.9	4.1	3.5	3.0	3.9	3.3	2.8	2.4	1.3		
等価発光面積		cm <sup>2</sup>	2.0	7.1	6.2	5.4	4.7	6.5	5.7	4.9	4.3	5.4	4.7	4.1	3.6	4.3	3.7	3.3	2.9	1.7	
取付高さ	器具間隔最大限		2.5	7.5	6.6	5.9	5.3	6.9	6.1	5.4	4.9	5.7	5.1	4.5	4.1	4.6	4.1	3.7	3.3	2.1	
	横方向 (A)	縦方向 (B)	3.0	7.8	7.0	6.3	5.7	7.2	6.5	5.8	5.3	5.9	5.4	4.9	4.5	4.8	4.4	4.0	3.6	2.3	
H m	0.00 H m	1.55 H m	4.0	8.2	7.5	6.9	6.4	7.5	6.9	6.4	5.9	6.3	5.8	5.4	5.0	5.1	4.7	4.4	4.1	2.7	
			5.0	8.4	7.9	7.3	6.9	7.8	7.3	6.8	6.4	6.5	6.1	5.7	5.4	5.3	5.0	4.7	4.4	3.0	
			7.0	8.7	8.3	7.8	7.5	8.1	7.7	7.3	6.9	6.8	6.5	6.2	5.9	5.6	5.3	5.1	4.9	3.4	
			10.0	9.0	8.6	8.3	8.0	8.3	8.0	7.7	7.4	7.0	6.8	6.6	6.3	5.8	5.6	5.5	5.3	3.7	

