

屋内照明器具特性	
品番 (品名)	LGB51550
光源	LED5000_70_850 ×1 850.0 lm
管理番号	K0142039 (0) DB 1
BZ分類	BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束 下方光束		4 % 96 %	室指数	照明率 (X0.01) ZCM																		
保守率		良 中 否	0.63	0.6	56	44	36	31	55	43	36	30	52	42	35	30	49	40	34	30	27	
			0.6	0.8	66	54	47	41	64	54	46	41	61	52	45	40	58	50	44	40	37	
			0.56	1.0	73	62	54	48	71	61	53	48	67	59	52	47	64	57	51	47	44	
				1.25	78	69	61	56	77	68	61	55	73	65	59	54	70	63	58	53	51	
下方投影面積		cm ²	1.5	83	74	67	61	81	72	66	61	77	70	64	60	73	68	63	59	56		
等価発光面積		cm ²	2.0	88	81	75	70	86	79	74	69	82	77	72	68	79	74	70	66	63		
取付 高さ	器具間隔最大限		2.5	92	85	80	75	90	84	79	75	86	81	77	73	82	78	75	71	68		
	横方向 (A) 縦方向 (B)		3.0	94	89	84	80	92	87	83	79	88	84	80	77	85	81	78	75	72		
H m	1.27 H m	1.27 H m	4.0	97	93	89	85	95	91	88	84	92	88	85	82	88	85	83	80	77		
			5.0	99	95	92	89	97	94	91	88	94	91	88	86	90	88	86	84	80		
			7.0	101	99	96	94	100	97	95	92	96	94	92	90	93	91	89	88	84		
			10.0	103	101	99	97	101	99	98	96	98	96	95	93	95	93	92	91	87		

