

屋内照明器具特性	
品番 (品名)	L G B 8 1 5 8 8
光源	L G B 8 1 5 8 8 - 4 0 D E G (H 1) × 1 7 8 5 . 0 l m
管理番号	K 0 1 3 6 1 1 3 (0) D R 1
B Z 分類	B Z 8 / 1 . 8 / B Z 9 / 4 . 5 / B Z 1

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束 下方光束		74 % 26 %	室指数	照明率 (X0.01) ZCM																	
保守率		良 中 否	0.67	0.6	44	33	26	21	39	29	23	18	30	22	18	14	21	16	13	10	4
			0.63	0.8	52	41	33	28	46	36	30	25	35	28	23	19	25	20	17	14	5
			1.0	57	47	39	34	51	42	35	30	39	32	27	24	27	23	20	17	6	
			0.56	1.25	63	53	46	40	55	47	41	36	42	36	32	28	30	26	23	20	8
下方投影面積		cm ²	1.5	66	57	50	45	59	51	45	40	45	39	35	31	32	28	25	22	9	
等価発光面積			2.0	71	64	57	52	63	57	51	47	48	44	40	36	35	31	28	26	11	
取付 高さ	器具間隔最大限		2.5	75	68	62	57	67	61	56	51	51	47	43	40	36	34	31	29	12	
	横方向 (A) 縦方向 (B)		3.0	77	71	66	61	69	63	59	55	53	49	46	43	38	35	33	31	13	
1.5m	2.01 m	1.99 m	4.0	80	75	70	66	72	67	63	60	55	52	49	46	40	38	36	34	15	
2	2.65	2.6	5.0	82	78	74	70	73	70	66	63	57	54	51	49	41	39	37	36	16	
2.5	3.3	3.22	7.0	84	81	78	75	76	73	70	67	59	56	54	53	43	41	40	38	17	
3	3.99	3.83	10.0	86	84	81	79	77	75	73	71	60	59	57	55	44	43	42	41	19	

