

# 屋内照明器具特性

品番 (品名)	LGB12602				
光源	LGB12602 ×1	3610.0 lm			
管理番号	K0127848 (0) DB 1				
BZ分類	BZ5 / 1.4 / BZ4				

器具効率	100%	天井	80%				70%				50%				30%				0%	
	上方光束 3%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	97%	床		10%				10%				10%				10%				0%
室指数		照明率 ( X0.01 )																		ZCM
保守率	良	0.67	0.6	5.6	4.4	3.6	3.1	5.5	4.3	3.6	3.1	5.2	4.2	3.5	3.0	5.0	4.1	3.5	3.0	2.8
	中	0.63	0.8	6.7	5.5	4.7	4.2	6.5	5.4	4.7	4.1	6.2	5.3	4.6	4.1	5.9	5.1	4.5	4.1	3.8
	否	0.56	1.0	7.3	6.3	5.5	5.0	7.2	6.2	5.5	4.9	6.8	6.0	5.4	4.9	6.5	5.8	5.2	4.8	4.6
			1.25	8.0	7.0	6.3	5.7	7.8	6.9	6.2	5.7	7.4	6.7	6.1	5.6	7.1	6.5	6.0	5.5	5.3
下方投影面積	cm <sup>2</sup>		1.5	8.4	7.5	6.9	6.3	8.2	7.4	6.8	6.3	7.8	7.2	6.6	6.2	7.5	7.0	6.5	6.1	5.8
等価発光面積	cm <sup>2</sup>		2.0	8.9	8.2	7.7	7.2	8.8	8.1	7.6	7.1	8.4	7.9	7.4	7.0	8.1	7.6	7.2	6.9	6.6
取付高さ	器具間隔最大限		2.5	9.3	8.7	8.2	7.8	9.1	8.6	8.1	7.7	8.8	8.3	7.9	7.6	8.5	8.1	7.7	7.4	7.1
	横方向 (A)	縦方向 (B)	3.0	9.5	9.0	8.6	8.2	9.4	8.9	8.5	8.1	9.0	8.6	8.3	8.0	8.7	8.4	8.1	7.8	7.5
1.5m	2m	2.01m	4.0	9.8	9.4	9.1	8.7	9.7	9.3	9.0	8.7	9.3	9.0	8.7	8.5	9.0	8.8	8.5	8.3	8.0
2	2.63	2.63	5.0	10.0	9.7	9.4	9.1	9.9	9.5	9.3	9.0	9.5	9.3	9.0	8.8	9.2	9.0	8.8	8.6	8.3
2.5	3.27	3.28	7.0	10.2	10.0	9.7	9.5	10.1	9.8	9.6	9.4	9.7	9.6	9.4	9.2	9.4	9.3	9.1	9.0	8.6
3	3.92	3.93	10.0	10.4	10.2	10.0	9.9	10.2	10.1	9.9	9.8	9.9	9.8	9.6	9.5	9.6	9.5	9.4	9.3	8.9

