

屋内照明器具特性	
品番 (品名)	LGB14602
光源	LGB14602 ×1 4750.0 lm
管理番号	K0127840(0)DB1
BZ分類	BZ5/1.8/BZ4

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	3%	床	10%				10%				10%				10%				0%	
下方光束	97%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	5.6	4.4	3.6	3.0	5.5	4.3	3.6	3.0	5.2	4.2	3.5	3.0	4.9	4.0	3.4	3.0	2.8
	中	0.63	0.8	6.6	5.5	4.7	4.1	6.5	5.4	4.6	4.1	6.1	5.2	4.5	4.0	5.9	5.1	4.5	4.0	3.8
	否	0.56	1.0	7.3	6.2	5.5	4.9	7.1	6.1	5.4	4.9	6.8	5.9	5.3	4.8	6.5	5.8	5.2	4.7	4.5
			1.25	7.9	7.0	6.2	5.7	7.7	6.8	6.2	5.6	7.4	6.6	6.0	5.6	7.1	6.4	5.9	5.5	5.2
下方投影面積		cm ²	1.5	8.3	7.5	6.8	6.3	8.2	7.4	6.7	6.2	7.8	7.1	6.6	6.1	7.5	6.9	6.4	6.0	5.7
等価発光面積		cm ²	2.0	8.9	8.2	7.6	7.1	8.7	8.1	7.5	7.1	8.4	7.8	7.3	6.9	8.0	7.6	7.2	6.8	6.5
取付高さ	器具間隔最大限		2.5	9.3	8.7	8.1	7.7	9.1	8.5	8.0	7.6	8.7	8.3	7.9	7.5	8.4	8.0	7.7	7.4	7.0
	横方向 (A)	縦方向 (B)	3.0	9.5	9.0	8.5	8.1	9.3	8.8	8.4	8.1	9.0	8.6	8.2	7.9	8.7	8.3	8.0	7.7	7.4
1.5m	2.01m	2.01m	4.0	9.8	9.4	9.0	8.7	9.6	9.3	8.9	8.6	9.3	9.0	8.7	8.4	9.0	8.7	8.5	8.3	7.9
2	2.63	2.63	5.0	10.0	9.7	9.4	9.1	9.8	9.5	9.2	9.0	9.5	9.2	9.0	8.8	9.2	9.0	8.8	8.6	8.2
2.5	3.28	3.28	7.0	10.2	10.0	9.7	9.5	10.0	9.8	9.6	9.4	9.7	9.5	9.3	9.2	9.4	9.3	9.1	9.0	8.6
3	3.93	3.93	10.0	10.4	10.2	10.0	9.9	10.2	10.0	9.9	9.7	9.9	9.8	9.6	9.5	9.6	9.5	9.4	9.3	8.9

