

屋内照明器具特性	
品番 (品名)	L G W8 0 2 4 6
光源	LED2700_70_95 x1 95.0 l m
管理番号	K0136362 (0) DB 1
B Z 分類	BZ7 / 0.7 / BZ6

器具効率		1 0 0 % 上方光束 5 % 下方光束 9 5 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6	5 0	3 7	2 8	2 2	4 9	3 6	2 8	2 2	4 5	3 4	2 7	2 2	4 3	3 3	2 6	2 1	1 9	
			0 . 6	6 0	4 7	3 8	3 1	5 8	4 6	3 7	3 1	5 4	4 4	3 6	3 0	5 1	4 2	3 5	3 0	2 7	
			1 . 0	6 6	5 4	4 5	3 8	6 4	5 2	4 4	3 7	6 0	5 0	4 3	3 7	5 6	4 8	4 1	3 6	3 3	
			0 . 5 6	1 . 2 5	7 2	6 0	5 2	4 5	7 0	5 9	5 1	4 4	6 6	5 6	4 9	4 4	6 2	5 4	4 8	4 3	3 9
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	7 6	6 6	5 7	5 1	7 4	6 4	5 6	5 0	7 0	6 1	5 4	4 9	6 6	5 9	5 3	4 8	4 4	
			2 . 0	8 3	7 3	6 6	5 9	8 0	7 2	6 4	5 8	7 6	6 8	6 2	5 7	7 2	6 6	6 0	5 6	5 2	
			2 . 5	8 6	7 8	7 1	6 5	8 4	7 7	7 0	6 5	8 0	7 3	6 8	6 3	7 6	7 0	6 6	6 1	5 8	
取付 高さ	器具間隔最大限		3 . 0	8 9	8 2	7 6	7 0	8 7	8 0	7 4	6 9	8 3	7 7	7 2	6 7	7 9	7 4	7 0	6 6	6 2	
	横方向 (A)	縦方向 (B)	4 . 0	9 3	8 7	8 2	7 7	9 1	8 5	8 0	7 6	8 7	8 2	7 8	7 4	8 3	7 9	7 5	7 2	6 8	
H m	1 . 4 6 H m	1 . 4 6 H m	5 . 0	9 5	9 0	8 6	8 1	9 3	8 9	8 4	8 0	8 9	8 5	8 1	7 8	8 5	8 2	7 9	7 6	7 2	
			7 . 0	9 8	9 4	9 1	8 7	9 6	9 3	8 9	8 6	9 2	8 9	8 6	8 3	8 8	8 6	8 3	8 1	7 7	
			1 0 . 0	1 0 1	9 8	9 5	9 2	9 9	9 6	9 3	9 1	9 5	9 2	9 0	8 8	9 1	8 9	8 7	8 5	8 1	

