

屋内照明器具特性	
品番 (品名)	L G W8 0 2 5 0
光源	LED2700_70_304 x1 304.0 l m
管理番号	K0136364 (0) DB 1
B Z 分類	B Z 6

器具効率		9 1 % 上方光束 2 3 % 下方光束 6 8 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
			室指数	照明率 (X 0 . 0 1) Z C M																				
保守率		良 中 否	0 . 6 3	0 . 6	0 . 6	0 . 5 6	0 . 6	4 7	3 5	2 8	2 3	4 4	3 4	2 7	2 3	4 0	3 1	2 6	2 1	3 6	2 9	2 4	2 0	1 7
			0 . 6	0 . 8	5 5	4 4	3 7	3 1	5 2	4 2	3 5	3 0	4 7	3 9	3 3	2 9	4 2	3 5	3 0	2 7	2 3			
			0 . 5 6	1 . 0	6 0	5 0	4 3	3 7	5 7	4 8	4 1	3 6	5 2	4 4	3 8	3 4	4 6	4 0	3 5	3 2	2 7			
			1 . 2 5	6 5	5 6	4 9	4 3	6 2	5 4	4 7	4 2	5 6	4 9	4 4	3 9	5 0	4 5	4 0	3 6	3 1				
下方投影面積		c m ²	1 . 5	6 9	6 0	5 3	4 8	6 6	5 8	5 1	4 6	5 9	5 3	4 8	4 3	5 3	4 8	4 4	4 0	3 4				
等価発光面積			c m ²	2 . 0	7 4	6 6	6 0	5 5	7 0	6 4	5 8	5 3	6 4	5 8	5 3	5 0	5 7	5 3	4 9	4 6	3 9			
				2 . 5	7 7	7 0	6 5	6 0	7 4	6 8	6 2	5 8	6 7	6 2	5 8	5 4	6 0	5 6	5 3	5 0	4 3			
取付 高さ	器具間隔最大限		3 . 0	7 9	7 3	6 8	6 4	7 6	7 0	6 6	6 2	6 9	6 4	6 1	5 7	6 2	5 9	5 6	5 3	4 6				
	横方向 (A)		縦方向 (B)		4 . 0	8 2	7 8	7 3	6 9	7 9	7 4	7 0	6 7	7 2	6 8	6 5	6 2	6 5	6 2	6 0	5 7	5 0		
H m	1 . 2 6 H m		1 . 2 5 H m		5 . 0	8 4	8 0	7 6	7 3	8 1	7 7	7 3	7 0	7 4	7 1	6 8	6 5	6 7	6 4	6 2	6 0	5 2		
					7 . 0	8 7	8 3	8 0	7 8	8 3	8 0	7 7	7 5	7 6	7 3	7 1	6 9	6 9	6 7	6 5	6 4	5 5		
					1 0 . 0	8 8	8 6	8 4	8 1	8 5	8 2	8 0	7 8	7 8	7 6	7 4	7 3	7 1	7 0	6 8	6 7	5 8		

