

屋内照明器具特性	
品番 (品名)	L G W8 0 2 5 5
光源	L E D 2 7 0 0 _ 7 0 _ 3 1 5 × 1 3 1 5 . 0 l m
管理番号	K 0 1 3 6 3 6 3 (0) D B 1
B Z 分類	B Z 5

器具効率		1 0 0 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		1 0 %	室指数	照明率 (X 0 . 0 1)																		Z C M	
下方光束		9 0 %																					
保守率		良	0 . 6 3	0 . 6	5 6	4 4	3 6	3 1	5 4	4 3	3 6	3 0	5 1	4 1	3 4	3 0	4 8	3 9	3 3	2 9	2 7		
		中	0 . 6	0 . 8	6 5	5 4	4 6	4 0	6 3	5 3	4 5	4 0	5 9	5 0	4 4	3 9	5 6	4 8	4 2	3 8	3 5		
		否	0 . 5 6	1 . 0	7 2	6 1	5 3	4 8	6 9	6 0	5 3	4 7	6 5	5 7	5 1	4 6	6 2	5 5	4 9	4 5	4 2		
				1 . 2 5	7 8	6 8	6 1	5 5	7 5	6 6	5 9	5 4	7 1	6 3	5 7	5 3	6 7	6 0	5 5	5 1	4 8		
下方投影面積		c m ²		1 . 5	8 2	7 3	6 6	6 1	7 9	7 1	6 5	6 0	7 5	6 8	6 3	5 8	7 1	6 5	6 0	5 6	5 3		
等価発光面積		c m ²		2 . 0	8 7	8 0	7 4	6 9	8 5	7 8	7 2	6 8	8 0	7 4	7 0	6 6	7 6	7 1	6 7	6 4	6 0		
取付	器具間隔最大限			2 . 5	9 1	8 4	7 9	7 4	8 8	8 2	7 7	7 3	8 4	7 9	7 4	7 1	7 9	7 5	7 2	6 9	6 4		
高さ	横方向 (A)		縦方向 (B)	3 . 0	9 3	8 7	8 3	7 8	9 1	8 5	8 1	7 7	8 6	8 2	7 8	7 5	8 2	7 8	7 5	7 2	6 8		
H m	0 . 0 0 H m		0 . 0 0 H m	4 . 0	9 6	9 1	8 7	8 4	9 4	8 9	8 6	8 2	8 9	8 6	8 2	8 0	8 5	8 2	7 9	7 7	7 2		
				5 . 0	9 8	9 4	9 1	8 8	9 5	9 2	8 9	8 6	9 1	8 8	8 5	8 3	8 7	8 4	8 2	8 0	7 5		
				7 . 0	1 0 0	9 7	9 4	9 2	9 8	9 5	9 3	9 0	9 3	9 1	8 9	8 7	8 9	8 7	8 5	8 4	7 9		
				1 0 . 0	1 0 2	1 0 0	9 8	9 6	9 9	9 7	9 6	9 4	9 5	9 3	9 2	9 0	9 1	8 9	8 8	8 7	8 2		

