

屋内照明器具特性	
品番 (品名)	L G W C 8 0 2 4 6
光源	LED2700_70_95 x1 95.0 l m
管理番号	K0136362 (0) DB 1
B Z 分類	BZ7 / 0.7 / BZ6

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.63	0.6	50	37	28	22	49	36	28	22	45	34	27	22	43	33	26	21	19
			0.6	0.8	60	47	38	31	58	46	37	31	54	44	36	30	51	42	35	30	27
			0.56	1.0	66	54	45	38	64	52	44	37	60	50	43	37	56	48	41	36	33
				1.25	72	60	52	45	70	59	51	44	66	56	49	44	62	54	48	43	39
下方投影面積 等価発光面積		cm ² cm ²		1.5	76	66	57	51	74	64	56	50	70	61	54	49	66	59	53	48	44
				2.0	83	73	66	59	80	72	64	58	76	68	62	57	72	66	60	56	52
				2.5	86	78	71	65	84	77	70	65	80	73	68	63	76	70	66	61	58
取付 高さ	器具間隔最大限			3.0	89	82	76	70	87	80	74	69	83	77	72	67	79	74	70	66	62
	横方向 (A)	縦方向 (B)		4.0	93	87	82	77	91	85	80	76	87	82	78	74	83	79	75	72	68
H m	1.46 H m	1.46 H m		5.0	95	90	86	81	93	89	84	80	89	85	81	78	85	82	79	76	72
				7.0	98	94	91	87	96	93	89	86	92	89	86	83	88	86	83	81	77
				10.0	101	98	95	92	99	96	93	91	95	92	90	88	91	89	87	85	81

