

屋内照明器具特性	
品番 (品名)	L S E B 2 0 2 6
光源	LED2700_70_780 ×1 780.0 l m
管理番号	K0142039 (0) DB 1
B Z 分類	B Z 5

器具効率		100 % 上方光束 4 % 下方光束 96 %		反射率	天井	80 %				70 %				50 %				30 %				0 %
					壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
					床	10 %				10 %				10 %				10 %				0 %
					室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.63	0.6	56	44	36	31	55	43	36	30	52	42	35	30	49	40	34	30	27	
			0.6	0.8	66	54	47	41	64	54	46	41	61	52	45	40	58	50	44	40	37	
			0.56	1.0	73	62	54	48	71	61	53	48	67	59	52	47	64	57	51	47	44	
				1.25	78	69	61	56	77	68	61	55	73	65	59	54	70	63	58	53	51	
下方投影面積 等価発光面積		cm ² cm ²		1.5	83	74	67	61	81	72	66	61	77	70	64	60	73	68	63	59	56	
				2.0	88	81	75	70	86	79	74	69	82	77	72	68	79	74	70	66	63	
				2.5	92	85	80	75	90	84	79	75	86	81	77	73	82	78	75	71	68	
				3.0	94	89	84	80	92	87	83	79	88	84	80	77	85	81	78	75	72	
H m	1.27 H m	1.27 H m		4.0	97	93	89	85	95	91	88	84	92	88	85	82	88	85	83	80	77	
				5.0	99	95	92	89	97	94	91	88	94	91	88	86	90	88	86	84	80	
				7.0	101	99	96	94	100	97	95	92	96	94	92	90	93	91	89	88	84	
				10.0	103	101	99	97	101	99	98	96	98	96	95	93	95	93	92	91	87	

