

屋内照明器具特性	
品番 (品名)	L S E B 7 1 0 4
光源	LED5000_70_1100 ×1 1100.0 lm
管理番号	K0138505 (1) DB 1
B Z 分類	BZ6 / 0.7 / BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		17 %	室指数	照明率 (X0.01)																			Z	CM
下方光束		83 %																						
保守率		良 中 否	0.63	0.6	52	40	32	26	50	39	31	26	46	36	30	25	42	34	28	24	21			
			0.6	0.8	62	50	42	36	59	48	41	35	54	45	38	34	50	42	36	32	28			
			0.56	1.0	68	57	49	43	65	55	47	42	60	51	45	40	55	48	43	38	34			
				1.25	74	64	56	50	71	61	54	49	65	57	51	46	60	54	49	44	40			
下方投影面積		cm ²	1.5	78	68	61	55	75	66	59	54	69	62	56	51	64	58	53	49	44				
等価発光面積			cm ²	2.0	84	76	69	63	80	73	67	62	74	68	63	59	69	64	60	56	50			
取付高さ	器具間隔最大限		2.5	87	80	74	69	84	78	72	67	78	73	68	64	72	68	64	61	55				
	横方向 (A)		縦方向 (B)	3.0	90	84	78	74	87	81	76	72	80	76	72	68	75	71	68	64	58			
1.5m	2.12 m	1.88 m	4.0	93	88	84	80	90	85	81	77	84	80	77	73	78	75	72	69	63				
2	2.82	2.48	5.0	95	91	87	83	92	88	85	81	86	83	80	77	80	77	75	73	66				
2.5	3.54	3.08	7.0	98	94	91	88	94	91	89	86	88	86	84	81	83	81	79	77	70				
3	4.2	3.66	10.0	99	97	95	93	96	94	92	90	90	88	87	85	85	83	82	80	73				

