

屋内照明器具特性	
品番 (品名)	L S E B 7 1 0 5
光源	LED5000_70_1100 ×1 1100.0 lm
管理番号	K0139436 (1) DR 1
B Z 分類	BZ8 / 4.5 / BZ7 / 8.5 / BZ8

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		50 %	室指数	照明率 (X0.01)																		Z	C	M
下方光束		50 %																						
保守率		良 中 否	0.63	0.6	45	33	25	19	41	30	23	18	34	25	19	15	27	21	16	12	7			
			0.6	0.8	54	41	33	27	49	38	31	25	40	32	26	21	33	26	21	18	11			
				1.0	60	48	40	33	54	44	37	31	45	37	31	26	36	30	25	22	14			
			0.56	1.25	65	54	46	40	60	50	43	37	49	42	36	31	40	34	30	26	17			
下方投影面積		cm ²	1.5	69	59	51	45	63	54	47	42	52	46	40	35	43	37	33	29	19				
等価発光面積		cm ²	2.0	75	66	59	53	69	61	54	49	57	51	46	42	47	42	38	35	23				
取付 高さ	器具間隔最大限		2.5	78	71	64	58	72	65	59	54	60	55	50	46	49	45	42	39	26				
	横方向 (A) 縦方向 (B)		3.0	81	74	68	63	75	68	63	58	63	58	54	50	51	48	44	42	29				
1.5m	2.31 m	1.87 m	4.0	84	79	74	69	78	73	68	64	66	62	58	55	54	51	48	46	32				
2	3.09	2.47	5.0	87	82	77	73	80	76	72	68	68	64	61	58	56	53	51	49	34				
2.5	3.83	3.07	7.0	89	85	82	78	83	79	76	73	70	67	65	63	58	56	54	53	37				
3	4.61	3.66	10.0	91	88	86	83	85	82	80	77	72	70	68	66	60	59	57	56	40				

