

屋内照明器具特性	
品番 (品名)	L S E B 7 2 0 1
光源	LED2700_70_850 ×1 850.0 lm
管理番号	K0138505 (1) DB 1
B Z 分類	BZ6 / 0.7 / BZ5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		1 7 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		8 3 %																					
保守率		良 中 否	0 . 6 3	0 . 6	5 2	4 0	3 2	2 6	5 0	3 9	3 1	2 6	4 6	3 6	3 0	2 5	4 2	3 4	2 8	2 4	2 1		
			0 . 6	0 . 8	6 2	5 0	4 2	3 6	5 9	4 8	4 1	3 5	5 4	4 5	3 8	3 4	5 0	4 2	3 6	3 2	2 8		
			0 . 5 6	1 . 0	6 8	5 7	4 9	4 3	6 5	5 5	4 7	4 2	6 0	5 1	4 5	4 0	5 5	4 8	4 3	3 8	3 4		
				1 . 2 5	7 4	6 4	5 6	5 0	7 1	6 1	5 4	4 9	6 5	5 7	5 1	4 6	6 0	5 4	4 9	4 4	4 0		
下方投影面積		c m ²	1 . 5	7 8	6 8	6 1	5 5	7 5	6 6	5 9	5 4	6 9	6 2	5 6	5 1	6 4	5 8	5 3	4 9	4 4			
等価発光面積			c m ²	2 . 0	8 4	7 6	6 9	6 3	8 0	7 3	6 7	6 2	7 4	6 8	6 3	5 9	6 9	6 4	6 0	5 6	5 0		
取付 高さ	器具間隔最大限		2 . 5	8 7	8 0	7 4	6 9	8 4	7 8	7 2	6 7	7 8	7 3	6 8	6 4	7 2	6 8	6 4	6 1	5 5			
	横方向 (A)		縦方向 (B)	3 . 0	9 0	8 4	7 8	7 4	8 7	8 1	7 6	7 2	8 0	7 6	7 2	6 8	7 5	7 1	6 8	6 4	5 8		
1 . 5m	2 . 1 2 m	1 . 8 8 m	4 . 0	9 3	8 8	8 4	8 0	9 0	8 5	8 1	7 7	8 4	8 0	7 7	7 3	7 8	7 5	7 2	6 9	6 3			
2	2 . 8 2	2 . 4 8	5 . 0	9 5	9 1	8 7	8 3	9 2	8 8	8 5	8 1	8 6	8 3	8 0	7 7	8 0	7 7	7 5	7 3	6 6			
2 . 5	3 . 5 4	3 . 0 8	7 . 0	9 8	9 4	9 1	8 8	9 4	9 1	8 9	8 6	8 8	8 6	8 4	8 1	8 3	8 1	7 9	7 7	7 0			
3	4 . 2	3 . 6 6	1 0 . 0	9 9	9 7	9 5	9 3	9 6	9 4	9 2	9 0	9 0	8 8	8 7	8 5	8 5	8 3	8 2	8 0	7 3			

