

屋内照明器具特性	
品番 (品名)	L S E B 7 2 0 3
光源	LED2700_70_650 ×1 650.0 lm
管理番号	K0140471 (0) DB 1
B Z 分類	BZ6 / 0.7 / BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束 下方光束		17 % 83 %	室指数	照明率 (X0.01) Z CM																		
保守率		良 中 否	0.63	0.6	52	40	32	26	50	38	31	26	46	36	29	25	42	34	28	24	21	
			0.6	0.8	62	50	42	36	59	48	40	35	54	45	38	33	50	42	36	32	28	
			0.56	1.0	68	57	49	43	65	55	47	42	60	51	45	40	55	48	42	38	34	
			1.25	74	63	56	50	71	61	54	49	65	57	51	46	60	54	48	44	39		
下方投影面積		cm ²	1.5	78	68	61	55	75	66	59	54	69	62	56	51	64	58	53	49	44		
等価発光面積		cm ²	2.0	84	75	69	63	80	73	67	62	74	68	63	59	69	64	59	56	50		
取付 高さ	器具間隔最大限		2.5	87	80	74	69	84	77	72	67	78	72	68	64	72	68	64	61	55		
	横方向 (A) 縦方向 (B)		3.0	90	83	78	73	86	81	76	72	80	76	71	68	74	71	67	64	58		
1.5m	2.12 m	1.86 m	4.0	93	88	83	79	90	85	81	77	84	80	76	73	78	75	72	69	63		
2	2.84	2.47	5.0	95	91	87	83	92	88	84	81	86	82	80	77	80	77	75	73	66		
2.5	3.53	3.08	7.0	97	94	91	88	94	91	89	86	88	86	83	81	82	80	78	77	70		
3	4.24	3.69	10.0	99	97	95	92	96	94	92	90	90	88	87	85	84	83	81	80	73		

