

屋内照明器具特性	
品番 (品名)	L S E W2 0 0 4
光源	LED5000_70_450 ×1 450.0 l m
管理番号	K0139579 (0) DB 1
B Z 分類	B Z 6

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 3	0 . 6	5 1	3 8	3 0	2 4	4 8	3 7	2 9	2 4	4 4	3 4	2 8	2 3	4 0	3 2	2 6	2 2	1 8
			0 . 6	0 . 8	6 0	4 8	4 0	3 4	5 7	4 6	3 8	3 3	5 2	4 3	3 6	3 1	4 8	4 0	3 4	2 9	2 6
			0 . 5 6	1 . 0	6 6	5 5	4 7	4 0	6 3	5 3	4 5	3 9	5 8	4 9	4 2	3 7	5 3	4 5	4 0	3 5	3 1
				1 . 2 5	7 2	6 2	5 4	4 7	6 9	5 9	5 2	4 6	6 3	5 5	4 9	4 4	5 8	5 1	4 6	4 1	3 6
下方投影面積		c m ²	1 . 5	7 6	6 7	5 9	5 3	7 3	6 4	5 7	5 1	6 7	5 9	5 3	4 9	6 1	5 5	5 0	4 6	4 0	
			等価発光面積	c m ²	2 . 0	8 2	7 4	6 7	6 1	7 9	7 1	6 5	5 9	7 2	6 6	6 1	5 6	6 6	6 1	5 7	5 3
取付 高さ	器具間隔最大限		2 . 5	8 6	7 8	7 2	6 7	8 2	7 6	7 0	6 5	7 6	7 0	6 5	6 1	7 0	6 5	6 1	5 8	5 1	
	横方向 (A) 縦方向 (B)		3 . 0	8 8	8 2	7 6	7 1	8 5	7 9	7 4	6 9	7 8	7 3	6 9	6 5	7 2	6 8	6 5	6 1	5 5	
H m	1 . 3 9 H m	1 . 3 9 H m	4 . 0	9 2	8 6	8 2	7 7	8 8	8 3	7 9	7 5	8 2	7 8	7 4	7 1	7 5	7 2	6 9	6 6	5 9	
			5 . 0	9 4	8 9	8 5	8 1	9 0	8 6	8 3	7 9	8 4	8 0	7 7	7 4	7 8	7 5	7 2	7 0	6 2	
			7 . 0	9 6	9 3	9 0	8 7	9 3	9 0	8 7	8 4	8 6	8 4	8 1	7 9	8 0	7 8	7 6	7 4	6 6	
			1 0 . 0	9 9	9 6	9 3	9 1	9 5	9 3	9 0	8 8	8 9	8 7	8 5	8 3	8 2	8 1	7 9	7 8	7 0	

