

屋内照明器具特性

品番 (品名)	LGB52690									
光源	LED5000_70_2320 x1 2320.0 1m									
管理番号	K0140350(1)DB1									
BZ分類	BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	5%	室指数	照明率 (X0.01)																ZCM		
下方光束	95%																				
保守率	良 中 否 0.63 0.6 0.56	0.6	56	44	36	31	55	43	36	31	52	42	35	30	49	40	34	30	28		
		0.8	66	55	47	41	64	54	46	41	61	52	45	40	58	50	44	40	37		
		1.0	72	62	54	48	71	61	53	48	67	58	52	47	64	56	51	46	44		
		1.25	78	69	61	56	76	67	61	55	73	65	59	54	69	63	57	53	50		
下方投影面積	c m ²	1.5	82	74	67	61	80	72	66	61	76	70	64	59	73	67	62	58	55		
		2.0	88	80	74	69	86	79	73	69	82	76	71	67	78	73	69	66	62		
取付高さ	器具間隔最大限		2.5	91	85	80	75	89	83	78	74	85	80	76	72	82	78	74	71	67	
	横方向 (A)	縦方向 (B)	3.0	94	88	83	79	92	87	82	78	88	84	80	76	84	81	77	75	71	
H m	1.24 H m	1.24 H m	4.0	97	92	88	85	95	91	87	84	91	88	84	82	88	85	82	80	76	
			5.0	99	95	92	89	97	93	90	87	93	90	88	85	90	87	85	83	79	
			7.0	101	98	96	93	99	97	94	92	95	93	91	89	92	90	88	87	83	
			10.0	103	101	99	97	101	99	97	95	97	96	94	93	94	93	91	90	86	

