

屋内照明器具特性	
品番 (品名)	NNF 4 1 8 7 7
光源	LED_FULL3500_85_4450 ×1 4450.0 lm
管理番号	K0135881 (0) DB 1
BZ分類	BZ4/0.7/BZ3/8.5/BZ4

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		6 3 %	室指数	照明率 (X 0 . 0 1) Z C M																		
下方光束		3 7 %																				
保守率		良 中 否	0 . 8 3	0 . 6	5 0	3 9	3 2	2 8	4 5	3 6	3 0	2 6	3 7	3 0	2 6	2 2	2 9	2 5	2 1	1 9	1 3	
			0 . 8 1	0 . 8	5 9	4 8	4 2	3 7	5 3	4 5	3 9	3 4	4 4	3 7	3 3	2 9	3 5	3 0	2 7	2 5	1 7	
			0 . 7 7	1 . 0	6 4	5 5	4 9	4 4	5 9	5 1	4 5	4 1	4 8	4 2	3 8	3 5	3 8	3 4	3 1	2 9	2 0	
				1 . 2 5	7 0	6 1	5 5	5 0	6 4	5 6	5 1	4 7	5 2	4 7	4 3	4 0	4 1	3 8	3 5	3 3	2 2	
下方投影面積		cm ²	1 . 5	7 3	6 6	6 0	5 5	6 7	6 0	5 5	5 1	5 5	5 0	4 6	4 3	4 4	4 0	3 8	3 6	2 4		
等価発光面積		cm ²	2 . 0	7 8	7 2	6 7	6 3	7 1	6 6	6 2	5 8	5 8	5 5	5 2	4 9	4 6	4 4	4 2	4 0	2 7		
取付 高さ	器具間隔最大限		2 . 5	8 1	7 6	7 1	6 8	7 4	7 0	6 6	6 2	6 1	5 8	5 5	5 2	4 8	4 6	4 4	4 3	2 8		
	横方向 (A) 縦方向 (B)		3 . 0	8 3	7 9	7 5	7 1	7 6	7 2	6 9	6 6	6 3	6 0	5 7	5 5	5 0	4 8	4 6	4 5	2 9		
1 . 5m	1 . 2 5 m	2 . 0 4 m	4 . 0	8 6	8 2	7 9	7 6	7 9	7 6	7 3	7 0	6 5	6 2	6 0	5 9	5 1	5 0	4 9	4 7	3 1		
2	1 . 6 6	2 . 6 2	5 . 0	8 8	8 5	8 2	7 9	8 0	7 8	7 5	7 3	6 6	6 4	6 2	6 1	5 2	5 1	5 0	4 9	3 2		
2 . 5	2 . 0 7	3 . 2 4	7 . 0	9 0	8 7	8 5	8 3	8 2	8 0	7 8	7 7	6 7	6 6	6 5	6 4	5 4	5 3	5 2	5 1	3 3		
3	2 . 4 9	3 . 8 5	1 0 . 0	9 1	8 9	8 8	8 6	8 3	8 2	8 1	7 9	6 9	6 8	6 7	6 6	5 5	5 4	5 3	5 3	3 4		

