

# 屋内照明器具特性

品番 (品名)	LGB52651														
光源	LED2700_70_2315 x1 2315.0 lm														
管理番号	K0140345(0)DR1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%				0%
上方光束	7%	室指数																			
下方光束	93%	照明率 ( X0.01)																			
保守率	良 0.63 中 0.6 否 0.56	0.6	5.5	4.3	3.5	3.0	5.3	4.2	3.5	2.9	5.0	4.0	3.4	2.9	4.8	3.9	3.3	2.8	2.6		
		0.8	6.5	5.3	4.5	3.9	6.3	5.2	4.4	3.9	5.9	5.0	4.3	3.8	5.6	4.8	4.2	3.7	3.5		
下方投影面積	c m <sup>2</sup>	1.25	7.7	6.7	5.9	5.3	7.5	6.6	5.8	5.3	7.1	6.3	5.7	5.2	6.7	6.0	5.5	5.1	4.7		
		1.5	8.1	7.2	6.5	5.9	7.9	7.0	6.4	5.8	7.5	6.7	6.2	5.7	7.1	6.5	6.0	5.6	5.2		
等価発光面積	c m <sup>2</sup>	2.0	8.7	7.9	7.2	6.7	8.4	7.7	7.1	6.6	8.0	7.4	6.9	6.4	7.6	7.1	6.7	6.3	5.9		
		2.5	9.0	8.3	7.7	7.3	8.8	8.2	7.6	7.2	8.3	7.8	7.4	7.0	7.9	7.5	7.1	6.8	6.4		
取付高さ	器具間隔最大限		3.0	9.3	8.6	8.1	7.7	9.0	8.5	8.0	7.6	8.6	8.1	7.7	7.4	8.2	7.8	7.5	7.2		
	横方向 (A)	縦方向 (B)																			
H m	1.25 H m	1.25 H m	4.0	9.6	9.1	8.6	8.3	9.3	8.9	8.5	8.1	8.9	8.6	8.2	7.9	8.5	8.2	7.9	7.7		
			5.0	9.8	9.4	9.0	8.6	9.6	9.2	8.8	8.5	9.1	8.8	8.5	8.3	8.7	8.5	8.2	8.0		
			7.0	10.0	9.7	9.4	9.1	9.8	9.5	9.2	9.0	9.4	9.1	8.9	8.7	9.0	8.8	8.6	8.4		
			10.0	10.2	10.0	9.7	9.5	10.0	9.8	9.6	9.4	9.6	9.4	9.2	9.1	9.2	9.1	8.9	8.8		

