

屋内照明器具特性

品番 (品名)	L G W 8 0 2 3 7									
光源	LED2700_70_335 x1					335.0 l m				
管理番号	K0135012(0)DB1									
BZ分類	BZ5									

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	4%	床	10%				10%				10%				10%				0%	
下方光束	96%	室指数	照明率 (X0.01)																ZCM	
保守率	良	0.63	0.6	56	44	36	30	55	43	36	30	52	42	35	30	49	40	34	30	27
	中	0.6	0.8	66	55	47	41	65	54	47	41	62	52	46	41	59	51	45	40	38
	否	0.56	1.0	73	63	55	49	71	62	54	49	68	60	53	48	65	58	52	48	45
			1.25	79	70	63	57	77	69	62	57	74	66	60	56	71	64	59	55	52
下方投影面積	cm ²		1.5	83	75	68	63	82	73	67	62	78	71	66	61	75	69	64	60	57
等価発光面積	cm ²		2.0	89	82	76	71	87	80	75	70	83	78	73	69	80	75	71	68	65
取付高さ	器具間隔最大限		2.5	92	86	81	76	90	85	80	76	87	82	78	74	84	80	76	73	70
	横方向 (A)	縦方向 (B)	3.0	95	89	85	81	93	88	84	80	89	85	81	78	86	83	79	77	73
Hm	1.42Hm	1.42Hm	4.0	98	93	90	86	96	92	88	85	92	89	86	83	89	86	84	81	78
			5.0	100	96	93	90	98	94	91	89	94	92	89	87	91	89	87	85	81
			7.0	102	99	96	94	100	97	95	93	97	94	93	91	93	92	90	88	85
			10.0	103	101	99	98	102	100	98	96	98	97	95	94	95	94	93	92	88

