

屋内照明器具特性	
品番 (品名)	NNN12270
光源	LDA8L-D-G-E17/S/Z6 ×1 760.0 l m
管理番号	K0172779 (0) DB1
BZ分類	BZ8

器具効率		79 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		39 %	室指数	照明率 (X0.01)																	Z	C	M
下方光束		40 %																					
保守率		良	0.69	0.6	36	26	20	16	33	24	19	15	27	20	16	12	22	17	13	10	6		
		中	0.67	0.8	43	33	27	22	39	30	25	20	32	25	21	17	26	21	17	14	9		
		否	0.63	1.0	47	38	32	27	43	35	29	25	36	29	25	21	29	24	20	17	11		
				1.25	52	43	37	32	47	40	34	29	39	33	29	25	32	27	24	21	13		
下方投影面積		c m ²		1.5	55	47	41	36	50	43	38	33	42	36	32	28	34	30	26	23	15		
等価発光面積		c m ²		2.0	59	52	46	42	54	48	43	39	45	40	36	33	37	33	30	27	18		
取付高さ	器具間隔最大限			2.5	62	56	51	46	57	52	47	43	48	43	40	37	39	36	33	30	21		
	横方向 (A)		縦方向 (B)	3.0	64	58	54	50	59	54	50	46	49	46	42	39	40	38	35	33	22		
H m	1.55 H m	1.53 H m	4.0	67	62	58	54	62	57	54	51	52	49	46	43	43	40	38	36	25			
			5.0	68	64	61	58	63	60	57	54	53	51	48	46	44	42	40	38	27			
			7.0	70	67	65	62	65	63	60	58	55	53	51	49	46	44	43	41	29			
			10.0	72	70	68	66	67	65	63	61	57	55	54	52	48	46	45	44	31			

