

屋内照明器具特性	
品番 (品名)	NNN12270
光源	LDA6L-G-E17/D/S/K5 ×1 600.0 l m
管理番号	K0187852 (1) DB1
BZ分類	BZ8

器具効率		8 2 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		4 1 % 4 1 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否		0 . 6	3 7	2 7	2 0	1 6	3 4	2 5	1 9	1 5	2 8	2 1	1 6	1 3	2 2	1 7	1 3	1 0	6	
			0 . 8	4 4	3 4	2 7	2 2	4 0	3 1	2 5	2 1	3 3	2 6	2 1	1 8	2 7	2 1	1 7	1 4	9		
			1 . 0	4 9	3 9	3 2	2 7	4 4	3 6	3 0	2 5	3 7	3 0	2 5	2 1	3 0	2 5	2 1	1 8	1 1		
			0 . 6 3	1 . 2 5	5 3	4 4	3 8	3 2	4 9	4 1	3 5	3 0	4 0	3 4	2 9	2 6	3 2	2 8	2 4	2 1	1 4	
下方投影面積		c m ²	1 . 5	5 6	4 8	4 2	3 7	5 2	4 4	3 9	3 4	4 3	3 7	3 3	2 9	3 5	3 0	2 7	2 4	1 6		
等価発光面積		c m ²	2 . 0	6 1	5 4	4 8	4 3	5 6	5 0	4 4	4 0	4 7	4 2	3 7	3 4	3 8	3 4	3 1	2 8	1 9		
取付 高さ	器具間隔最大限		2 . 5	6 4	5 7	5 2	4 7	5 9	5 3	4 8	4 4	4 9	4 5	4 1	3 8	4 0	3 7	3 4	3 1	2 1		
	横方向 (A) 縦方向 (B)		3 . 0	6 6	6 0	5 5	5 1	6 1	5 6	5 1	4 7	5 1	4 7	4 4	4 0	4 2	3 9	3 6	3 4	2 3		
H m	1 . 6 0 H m	1 . 5 3 H m	4 . 0	6 9	6 4	6 0	5 6	6 3	5 9	5 6	5 2	5 3	5 0	4 7	4 5	4 4	4 1	3 9	3 7	2 6		
			5 . 0	7 1	6 6	6 3	5 9	6 5	6 2	5 8	5 5	5 5	5 2	5 0	4 7	4 5	4 3	4 1	3 9	2 8		
			7 . 0	7 3	7 0	6 7	6 4	6 7	6 5	6 2	5 9	5 7	5 5	5 3	5 1	4 7	4 6	4 4	4 3	3 0		
			1 0 . 0	7 4	7 2	7 0	6 8	6 9	6 7	6 5	6 3	5 9	5 7	5 5	5 4	4 9	4 8	4 6	4 5	3 2		

