

屋内照明器具特性	
品番 (品名)	NNN12280
光源	LDA8L-D-G-E17/S/Z6 ×1 760.0 l m
管理番号	K0172780 (0) DB1
BZ分類	BZ8

器具効率		7 4 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束		3 7 %	室指数	照明率 (X 0 . 0 1)																	Z C M
下方光束		3 7 %																			
保守率		良	0 . 6 9	0 . 6	3 4	2 4	1 9	1 5	3 1	2 3	1 7	1 4	2 5	1 9	1 5	1 1	2 0	1 5	1 2	9	5
		中	0 . 6 7	0 . 8	4 0	3 1	2 5	2 0	3 6	2 8	2 3	1 9	3 0	2 4	1 9	1 6	2 4	1 9	1 6	1 3	8
		否	0 . 6 3	1 . 0	4 4	3 5	2 9	2 5	4 0	3 3	2 7	2 3	3 3	2 7	2 3	1 9	2 7	2 2	1 9	1 6	1 0
		1 . 2 5	4 8	4 0	3 4	2 9	4 4	3 7	3 1	2 7	3 6	3 1	2 7	2 3	2 9	2 5	2 2	1 9	1 2		
下方投影面積		c m ²		1 . 5	5 1	4 4	3 8	3 3	4 7	4 0	3 5	3 1	3 9	3 4	2 9	2 6	3 1	2 7	2 4	2 2	1 4
等価発光面積		c m ²		2 . 0	5 5	4 9	4 3	3 9	5 1	4 5	4 0	3 6	4 2	3 8	3 4	3 1	3 4	3 1	2 8	2 5	1 7
取付高さ	器具間隔最大限			2 . 5	5 8	5 2	4 7	4 3	5 3	4 8	4 4	4 0	4 4	4 0	3 7	3 4	3 6	3 3	3 1	2 8	1 9
	横方向 (A)		縦方向 (B)	3 . 0	6 0	5 4	5 0	4 6	5 5	5 0	4 6	4 3	4 6	4 2	3 9	3 7	3 8	3 5	3 3	3 0	2 1
H m	1 . 4 5 H m	1 . 5 3 H m	4 . 0	6 2	5 8	5 4	5 1	5 7	5 4	5 0	4 7	4 8	4 5	4 3	4 0	4 0	3 7	3 5	3 3	2 3	
			5 . 0	6 4	6 0	5 7	5 4	5 9	5 6	5 3	5 0	5 0	4 7	4 5	4 3	4 1	3 9	3 7	3 6	2 5	
			7 . 0	6 6	6 3	6 0	5 8	6 1	5 8	5 6	5 4	5 2	5 0	4 8	4 6	4 3	4 1	4 0	3 8	2 7	
			1 0 . 0	6 7	6 5	6 3	6 1	6 3	6 1	5 9	5 7	5 3	5 2	5 0	4 9	4 4	4 3	4 2	4 1	2 9	

