

屋内照明器具特性	
品番 (品名)	NNN12280
光源	LDA5L-D-G-E17/S/Z4 ×1 440.0 l m
管理番号	K0159056 (0) DB1
BZ分類	BZ8

器具効率		67 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		34 %	室指数	照明率 (X0.01)																	Z	C	M
下方光束		33 %																					
保守率		良 中 否	0.69	0.6	30	22	17	13	28	20	16	12	23	17	13	10	18	14	11	8	5		
			0.67	0.8	36	28	22	18	33	26	21	17	27	21	17	14	22	17	14	12	7		
			0.63	1.0	40	32	26	22	36	29	24	21	30	25	21	17	24	20	17	14	9		
				1.25	43	36	31	26	40	33	28	25	33	28	24	21	26	23	20	17	11		
下方投影面積		cm ²	1.5	46	39	34	30	42	36	31	28	35	30	27	23	28	25	22	19	13			
等価発光面積		cm ²	2.0	50	44	39	35	46	40	36	32	38	34	30	28	31	28	25	23	15			
取付 高さ	器具間隔最大限		2.5	52	47	42	39	48	43	39	36	40	36	33	31	33	30	27	25	17			
	横方向 (A)	縦方向 (B)	3.0	54	49	45	42	50	45	42	39	41	38	35	33	34	32	29	27	19			
H m	1.45 H m	1.53 H m	4.0	56	52	49	46	52	48	45	42	44	41	38	36	36	34	32	30	21			
			5.0	57	54	51	48	53	50	48	45	45	43	40	38	37	35	34	32	22			
			7.0	59	57	54	52	55	53	50	48	47	45	43	41	39	37	36	35	25			
			10.0	61	59	57	55	56	55	53	51	48	47	45	44	40	39	38	37	26			

