

屋内照明器具特性	
品番 (品名)	NNN12280
光源	LDA6L-G-E17/D/S/K5 ×1 600.0 l m
管理番号	K0187853 (1) DB 1
BZ分類	BZ8

器具効率		77 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		38 %	室指数	照明率 (X0.01)																	Z	C	M
下方光束		39 %																					
保守率		良	0.69	0.6	35	25	19	15	32	23	18	14	26	20	15	12	21	16	12	10	6		
		中	0.67	0.8	41	32	26	21	38	29	24	19	31	25	20	16	25	20	16	14	8		
		否	0.63	1.0	46	37	30	26	42	34	28	24	35	28	24	20	28	23	19	17	10		
				1.25	50	42	35	30	46	38	33	28	38	32	28	24	31	26	23	20	13		
下方投影面積		cm ²		1.5	53	45	39	34	49	42	36	32	40	35	31	27	33	28	25	22	14		
等価発光面積		cm ²		2.0	57	51	45	40	53	47	42	37	44	39	35	32	36	32	29	26	17		
取付 高さ	器具間隔最大限			2.5	60	54	49	45	55	50	45	41	46	42	38	35	38	35	32	29	20		
	横方向 (A)		縦方向 (B)	3.0	62	57	52	48	57	52	48	45	48	44	41	38	39	36	34	32	21		
H _m	1.49 H _m	1.53 H _m	4.0	65	60	56	53	60	56	52	49	50	47	44	42	41	39	37	35	24			
			5.0	67	63	59	56	62	58	55	52	52	49	47	44	43	41	39	37	26			
			7.0	69	66	63	60	64	61	58	56	54	52	50	48	45	43	42	40	28			
			10.0	70	68	66	64	65	63	61	59	56	54	52	51	46	45	44	43	30			

