

屋内照明器具特性	
品番 (品名)	NNN12621B
光源	LDT8L-G/Z60/S/W ×1 810.0lm
管理番号	K0138598(0)DB1
BZ分類	BZ10

器具効率		60 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
				室指数	照明率 (X0.01) ZCM																				
保守率		良 中 否	0.63	0.6	0.56	0.6	25	17	12	9	23	16	11	8	18	13	9	6	14	10	7	5	2		
			0.6	0.8	30	22	17	13	27	20	15	12	22	16	12	9	17	13	10	7	3				
			1.0	33	26	20	16	30	24	19	15	25	19	15	12	19	15	12	9	5					
			1.25	37	29	24	20	33	27	22	18	27	22	18	15	21	18	14	12	6					
下方投影面積		cm ²	1.5	39	32	27	23	36	30	25	21	29	24	21	17	23	19	16	14	8					
等価発光面積			2.0	43	37	32	28	39	34	29	26	32	28	24	21	26	22	20	17	10					
取付 高さ			器具間隔最大限		2.5	45	40	35	31	41	37	32	29	34	30	27	24	28	25	22	20	12			
		横方向 (A)		縦方向 (B)		3.0	47	42	38	34	43	39	35	32	36	32	29	27	29	26	24	22	14		
		H m		0.00 H m		0.00 H m		4.0	49	45	41	38	45	42	38	35	38	35	32	30	31	29	27	25	16
						5.0	51	47	44	41	47	43	41	38	39	37	34	32	32	30	28	27	18		
						7.0	52	50	47	45	48	46	44	41	41	39	37	35	34	32	31	29	20		
				10.0	54	52	50	48	50	48	46	44	42	41	39	38	35	34	33	32	23				

