

屋内照明器具特性	
品番 (品名)	NNN1 2 6 2 1 W
光源	LDT8L - G / Z60 / S / W ×1 810.0 lm
管理番号	K0138598 (0) DB 1
BZ分類	BZ10

器具効率		60 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
上方光束		29 %	室指数	照明率 (X0.01)																				Z	CM
下方光束		31 %																							
保守率		良 中 否	0.63	0.6	25	17	12	9	23	16	11	8	18	13	9	6	14	10	7	5	2				
			0.6	0.8	30	22	17	13	27	20	15	12	22	16	12	9	17	13	10	7	3				
			0.56	1.0	33	26	20	16	30	24	19	15	25	19	15	12	19	15	12	9	5				
				1.25	37	29	24	20	33	27	22	18	27	22	18	15	21	18	14	12	6				
下方投影面積		cm ²	1.5	39	32	27	23	36	30	25	21	29	24	21	17	23	19	16	14	8					
等価発光面積		cm ²	2.0	43	37	32	28	39	34	29	26	32	28	24	21	26	22	20	17	10					
取付 高さ	器具間隔最大限		2.5	45	40	35	31	41	37	32	29	34	30	27	24	28	25	22	20	12					
	横方向 (A)	縦方向 (B)	3.0	47	42	38	34	43	39	35	32	36	32	29	27	29	26	24	22	14					
H m	0.00 H m	0.00 H m	4.0	49	45	41	38	45	42	38	35	38	35	32	30	31	29	27	25	16					
			5.0	51	47	44	41	47	43	41	38	39	37	34	32	32	30	28	27	18					
			7.0	52	50	47	45	48	46	44	41	41	39	37	35	34	32	31	29	20					
			10.0	54	52	50	48	50	48	46	44	42	41	39	38	35	34	33	32	23					

