

屋内照明器具特性

品番 (品名)	LGB71736														
光源	LED2700_70_380 x1 380.0 lm														
管理番号	K0139521(0)DB1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
				床	10%				10%				10%				10%			
上方光束	0%	室指数	照明率 (X0.01)																ZCM	
下方光束	100%																			
保守率	良 中 否	0.67	0.6	57	45	37	31	56	44	37	31	53	43	36	31	51	42	36	31	29
		0.63	0.8	66	55	47	41	65	54	47	41	62	53	46	41	60	51	45	41	38
			1.0	73	62	54	48	71	61	54	48	68	59	53	48	65	58	52	47	45
		0.56	1.25	79	69	61	55	77	68	61	55	74	66	60	55	71	64	59	54	52
下方投影面積	c m ²	1.5	83	74	66	61	81	73	66	61	78	71	65	60	75	69	64	59	57	
		2.0	88	81	74	69	87	79	74	69	83	77	72	68	80	75	71	67	65	
取付高さ	器具間隔最大限		2.5	92	85	80	75	90	84	79	74	87	82	77	73	84	80	76	72	70
	横方向 (A)	縦方向 (B)	3.0	94	89	84	79	93	87	83	79	90	85	81	78	87	83	80	76	74
H m	1.10 H m	1.05 H m	4.0	98	93	89	85	96	92	88	84	93	89	86	83	90	87	84	82	79
			5.0	100	96	92	89	98	94	91	88	95	92	89	87	93	90	88	85	83
			7.0	102	99	96	94	100	98	95	93	98	95	93	91	95	93	91	90	87
			10.0	104	102	100	98	102	100	98	97	100	98	96	95	97	96	94	93	90

